

Item no.: 362010

## 41432 - USB charger 1x USB Type-C™ PD 85 W + 3x USB Type-A, white

from **89,36 EUR**

Item no.: 362010  
shipping weight: 0.60 kg  
Manufacturer: Delock

### Product Description

This USB Power Delivery (PD) charger from Delock can be used to power notebooks with a USB Type-C™ connection. It provides various voltages from 5 V to 20 V and a power of up to 85 watts. In addition, 3 USB Type-A 5 V ports with Qualcomm Quick Charge 3.0 charging technology are available for smartphones. Due to the special charging technology, the power supply unit can also be used to power conventional notebooks. The scope of delivery includes 11 different DC adapters that are suitable for different notebooks. With this versatile power supply unit, all mobile devices can be charged at just one socket.

#### Specification

- Connections: 1 x USB Type-C™ socket, 3 x USB Type-A socket, 1 x small appliance inlet IEC-60320-C8
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2 A
- Output: USB Type-C™ Power Delivery (PD): 5 V / 4 A, 9 V / 12 V / 15 V / 20 V 4.3 A, USB Type-A Qualcomm Quick Charge 3.0 Class A: 3.6 ~ 6.5 V / 3 A, 9 V / 2 A, 12 V / 1.5 A
- Output power: max. 87 W total
- Overload protection
- Overcurrent protection
- Overheating protection
- Short-circuit protection
- Colour: white
- Dimensions (LxWxH): approx. 110 x 98 x 20 mm

#### Compatible with:

- N04 19 V 4.8 x 1.7 x 10.7 mm: HP/Compaq: 18.5 V / 2.7 A, 18.5 V / 3.5 A; Delta: 19 V / 2.64 A; ASUS: 19 V / 2.64 A; NEC: 19 V / 2.64 A
- N07 19 V 5.5 x 2.5 x 10.7 mm: Dell: 19 V / 3.16 A, 19 V / 3.42 A; Delta: 19 V / 2.64 A; Toshiba: 19 V / 3.16 A, 19 V / 3.42 A; LiteOn: 19 V / 3.16 A, 19 V / 3.42 A; NEC: 19 V / 2.64 A, 19 V / 3.16 A; Gateway: 19 V / 3.16 A, 19 V / 3.42 A
- N09 19.5 V 6.0 x 4.3 x 10.7 mm: Sony: 19.5 V / 2.7 A, 19.5 V / 3 A; Fujitsu: 19 V / 3.16 A; N11 19 V 5.5 x 1.7 x 10.7 mm; Acer: 19 V / 3.42 A; Delta: 20 V / 3.5 A
- N18 19 V 5.5 x 2.1 x 10.7 mm: Acer: 19 V / 3.16 A, 19 V / 3.42 A; LiteOn: 19 V / 3.16 A, 19 V / 3.42 A; NEC: 19 V / 3.16 A; N19 19 V 5.5 x 3.0 x 10.7 mm; Samsung: 19 V / 3.16 A
- N22 19.5 V 7.4 x 5.0 x 12.5 mm: Dell: 19.5 V / 3.34 A, 19.5 V / 4.62 A; N23 18.5 V 7.4 x 5.0 x 12.5 mm; HP/Compaq: 18.5 V / 3.5 A; N24 20 V 7.9 x 5.5 x 0.9 mm; IBM/Lenovo: 20 V / 3.25 A
- N35 20 V 11 x 5.6 x 11 mm: Lenovo: 20 V / 2.25 A, 20 V / 3.25 A; N36 19.5 V 4.5 x 3.0 mm; HP: 19.5 V / 2.31 A, 19.5 V / 3.33 A

#### Package contents

- USB cradle
- Power cable
- Carry case
- Stand
- USB Type-C™ PD cable, length approx. 1 m
- USB Type-C™ DC cable, length approx. 1 m
- 11 x DC adapter
- Instruction manual

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

