


Item no.: 361696

## Delock USB 2.0 to Serial LVTTTL Converter with 6 Single Pin Sockets 1.8m

from **16,73 EUR**

Item no.: 361696  
shipping weight: 0.10 kg  
Manufacturer: Delock



### Product Description

This USB 2.0 to TTL converter from Delock can be connected directly to GPIO (General purpose input / output) connectors or UART (Universal Asynchronous Receiver / Transmitter) interfaces. The converter is suitable for applications on single-board computers, controllers, FPGAs, MCUs and in circuit electronics etc.

#### Specification

- Connectors: 1x USB 2.0 type-A male > 1x TTL 3.3 V 6 pin male single
- Chipset: FTDI FT232RL
- Wire gauge: 26 AWG
- Compatible with UHCI / OHCI / EHCI controller
- Data transfer rate up to 3 Mbps
- Data bits: 7 or 8
- Stop bits: 1 or 2
- Parity: None, Space, Even, Odd, Marker
- Flow control: none, hardware RTS / CTS, software XON / XOFF
- FIFO: 128 bytes - RX, 256 bytes - TX
- Cable length incl. connections: approx. 1.8 m
- Operating temperature: -20 °C ~ 80 °C

#### System requirements

- Linux Kernel 2.6 or higher
- Mac OS 10.5 or higher
- Windows CE 4.2/5.0/6.0
- Windows XP/XP-64/Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC or notebook with a free USB type-A port

#### Package contents

- Converter USB 2.0 Serial TTL
- Driver CD
- Instruction manual

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

