

Item no.: 362135

## S/PDIF TOSLINK Switch 3 In 1 Out with IR Remote Control and USB Power Supply

from **14,79 EUR**

Item no.: 362135  
shipping weight: 0.10 kg  
Manufacturer: Delock



### Product Description

**Brief description** With this TOSLINK switch from Delock, up to three TOSLINK devices can be operated, e.g. on a home cinema system.

**Supports HD audio formats** The switch supports all common 2.0 and 5.1 audio formats such as LPCM, Dolby Digital, DTS Audio and thus offers a sound experience like in the cinema.

**High-resolution sampling rate** The switch offers a sampling rate of up to 24 bits and 96 kHz. This means that the sound can be reproduced loss-free in the High-Res Audio range.

**High transmission distance** The switch supports an output transmission distance of up to 40 m via an optical TOSLINK cable with a signal loss of less than 0.2 dB/m.

**Manual switching or with IR remote control** The switch can be switched or switched off by means of buttons on the unit or via the infrared remote control included in the scope of delivery. This allows the inputs to be switched easily and conveniently.

**Last Time Working State Memory** The switch automatically remembers the last working state when switched off and therefore uses the last selected input.

**USB power supply** The switch does not require an additional external power supply unit, power is supplied via the USB cable included in the scope of delivery.

**Specification**

- Connections - Input, 3x TOSLINK socket S/PDIF, 1x USB type Mini-B socket (5 V power supply), 1x 3.5 mm 3 pin jack socket (infrared input)
- Output - 1x TOSLINK socket S/PDIF
- Supported sampling rates: 32 / 44.1 / 48 / 96 kHz
- Bit rate 16 - 24 bit
- Baud rate: max. 16 Mbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supports signal retiming
- On/off switch
- Switch for changing the input source
- 3 x LED display (blue) for selected input
- Plastic housing
- Colour: black
- Dimensions (LxWxH): approx. 61 x 54 x 20 mm
- Voltage: 5 V
- Overvoltage protection
- USB bus power

**System requirements**

- Digital optical audio signal
- One free USB type-A socket

**Package contents**

- TOSLINK switch
- USB Type-A to Type Mini-B cable, length approx. 75 cm
- Infrared receiver with 3.5 mm jack plug, cable length approx. 60 cm
- Adhesive pad for infrared receiver
- Remote control
- Operating instructions

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

