


Item no.: 361597

USB 2.0 to Serial TTL converter with 6 open cable ends 1.8 m (3.3 V)

from **19,27 EUR**

Item no.: 361597
shipping weight: 0.10 kg
Manufacturer: Delock



Product Description

This USB 2.0 to TTL converter from Delock can be connected directly to GPIO (General purpose input / output) connectors or UART (Universal Asynchronous Receiver / Transmitter) interfaces. The converter is suitable for applications on single-board computers, controllers, FPGAs, MCUs and in circuit electronics etc.

Specification

- Connectors:
- 1 x USB 2.0 Type-A male >
- 1 x TTL 3.3 V 6 open cable ends
- Chipset: FTDI FT232RL
- Wire gauge: 26 AWG
- Compatible with UHCI / OHCI / EHCI controller
- Data transfer rate up to 3 Mbps
- Data bits: 7 or 8
- Stop bits: 1 or 2
- Parity: None, Space, Even, Odd, Marker
- Flow control: none, hardware RTS / CTS, software XON / XOFF
- FIFO:
- 128 bytes - RX
- 256 byte - TX
- Cable length incl. connections: approx. 1.8 m
- Operating temperature: -20 °C ~ 80 °C

System requirements

- Linux Kernel 2.6 or higher
- Mac OS 10.5 or higher
- Windows CE 4.2/5.0/6.0
- Windows XP/XP-64/Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC or notebook with a free USB type-A port

Package contents

- Converter USB 2.0 Serial TTL
- Driver CD
- Instruction manual

Packaging

- Retail Box

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



