

Item no.: 361885

Adapter cable USB type-A to serial RS-232 RJ10 with ESD protection 2 m

from **24,45 EUR**

shipping weight: 0.10 kg Manufacturer: Delock



Product Description

This USB to RS-232 RJ10 adapter cable from Delock is suitable for PC operation of handheld control boxes of the Meade Autostar telescopes. With the appropriate astronomy applications, the position of the telescopes can be controlled on the computer or a firmware update can be carried out. Compatible models:

- All DS models
- All DS2000 modelsAll ETX models

- All LX90 modelsAll LXD55 models
- All LXD75 models All LT models
- Connectors: 1x USB 2.0 type-A plug, 1x serial RS-232 RJ10 plug
 Chipset: FTDI FT231X

- Chipset: F1DI F1231X
 Plug & Play
 FIFO: 512 byte TX
 FIFO: 512 byte RX
 Compatible with USB 3.0, USB 2.0 and USB 1.1 full speed 12 Mbps
 Data transfer rate up to 230.4 Kb/s
 Signals: GND(1), RXD(3), TXD(4)
 FSD overvoltage protection IFC 61000.4-2

- ESD overvoltage protection IEC 61000-4-2
 HCP & VCP: ±4 kV

- Air discharge: ±8 kV
 Contact discharge: ±4 kV

- Cable length incl. connectors: approx. 2.0 m
 Suitable for various handheld control boxes from Meade Autostar



