

Item no.: 344200 **RELAYIO501 - Onsite Management Card**



shipping weight: 0.20 kg Manufacturer: CyberPower



Product Description

RELAYIO501 - Onsite Management Card

CyberPower RELAYI0501 is an optional management add-on to specific CyberPower UPS series. After inserting the card into the expansion port on the UPS, the card can execute multiple alerts whenever power issues occur, including UPS failures, overloads, over temperature etc. In addition, the card provides one input contact for remote UPS shutdown in battery mode.

Featuring a dry contact interface, the card is able to provide ON/OFF control of connected devices, such as triggering emergency alarms, exit lights, generators, and more. With its hot-swappable design, the UPS can remain ON while installing this product. General

- Power dissipation (Watts): 1.35
- Connector type: Hardwire terminal block
- Supports plug-and-play installation: Yes

Management & Communication

- Shut down UPS: Yes
- Dry contact relay (pcs.): 5

Physical

- Color: Black
- Dimensions (WxHxD, in.): 2.1 x 1.4 x 3.2
 Dimensions (WxHxD, mm.): 54 x 36.1 x 80.7
- Weight (lbs.): 0.11
 Weight (g.): 52

Environment

- Operating temperature (°F): 32 ~ 104
 Operating temperature (°C): 0 ~ 40
- Operating relative humidity (non-condensing, %): 0 ~ 95
 Operating elevation (feet/meters): 0-9,843 feet (0-3,000 meters)

- Storage temperature (°F): 5 ~ 113
 Storage temperature (°C): -15 ~ 45
 Storage relative humidity (non-condensing, %): 0 ~ 95
 Storage elevation (feet/meters): 0-49,213 feet (0-15,000 meters)

Certifications

- Certifications: FCC Class B
 RoHS: Yes
- Specifications



Scan this QR code to view the product All details, up-to-date prices and availability