

Item no.: 344123

BP48VP2U01 - Battery for UPS Systems (PR750ERTXL2U, PR1000ERTXL2U)

from **569,43 EUR**

Item no.: 344123
shipping weight: 29.80 kg
Manufacturer: CyberPower



Product Description

Battery Extension for UPS Systems (PR750ERTXL2U, PR1000ERTXL2U)

CyberPower BP48VP2U01 is an Extended Battery Module (EBM) which can be used in conjunction with compatible UPS systems to provide prolonged system runtime during power interruption. The battery module comes with DC plug-and-play power connectors to allow for adding multiple EBMs. With the built-in charger design, the EBMs can charge directly from utility without resorting to UPS, significantly saving total charging time when charging multiple EBMs.

The product features hot-swappable battery packs, allowing users to safely replace battery module without interrupting connected loads. The sealed lead-acid battery used within the EBM is stable and safe, which ensures the power system's reliable performance. Designed with industrial-grade metal enclosure, the product is suitable for data centers and critical applications.

General

- Nominal output voltage (Vdc): 48
- Rated output current (A): 60

Battery

- Battery type: Sealed lead-acid
- Battery quantity (pcs.): 8
- Single battery voltage (V): 12
- Single battery capacity (AH): 7
- Built-in charger: Yes
- Typical recharge time (hours): 6
- User-replaceable: Yes
- Hot-swappable: Yes
- Expansion ready: Yes
- Replacement battery pack: RBP0128
- Replacement battery pack quantity (pcs.): 2

Physical

- Form factor: Rackmount, tower
- Enclosure construction: Metal
- Color: Black
- Rackmount rail: Yes
- Rackmount ears: Yes

Physical Size

- Dimensions (WxHxD, in.): 17.1 x 3.4 x 16.2
- Dimensions (WxHxD, mm): 433 x 86.5 x 412
- Weight (lbs.): 55.8
- Weight (kg.): 25.3
- Installed rack height (U): 2

Environmental

- Operating temperature (°F): 32 ~ 104
- Operating temperature (°C): 0 ~ 40
- Operating relative humidity (non-condensing, %): 0 ~ 90
- Operating elevation (feet/meters): 0 - 9,843 feet (0 - 3,000 meters)
- Storage temperature (°F): 5 ~ 113
- Storage temperature (°C): -15 ~ 45
- Storage relative humidity (non-condensing, %): 0 ~ 95
- Storage elevation (feet/meters): 0 - 49,213 feet (0 - 15,000 meters)

Certifications

- Certifications: CE, FCC Class B, UL, RCM
- RoHS: Yes

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

