

Item no.: 361692

## Converter USB 2.0 type-A plug to serial TTL 3.5 mm 4 pin jack 1.8 m (3.3 V)

from **21,02 EUR**

Item no.: 361692  
shipping weight: 0.10 kg  
Manufacturer: Delock



### Product Description

This USB 2.0 to TTL converter from Delock can be connected directly to GPIO (General purpose input/output) connectors or UART (Universal Asynchronous Receiver/Transmitter) interfaces. The converter is suitable for applications on single-board computers, controllers, FPGAs, MCUs and in circuit electronics, etc.

- Connections: 1x USB 2.0 type-A plug > 1x TTL 3.3 V 3.5 mm jack plug
- Pin assignment: 1. TXD; 2. RXD; 3. GND; 4. VCC
- Chipset: FTDI FT232RL
- Wire cross-section: 28 AWG
- Compatible with UHCI/OHCI/EHCI controller
- Data transfer rate up to 3 Mbps
- Data bits: 7 or 8
- Stop bits: 1 or 2
- Parity: None, Space, Even, Odd, Marker
- Flow control: none, hardware RTS/CTS, software XON/XOFF
- FIFO: 128 bytes - RX, 256 bytes - TX
- Cable length incl. connections: approx. 1.8 m
- Operating temperature: -20°C ~ 80°C

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

