

Item no.: 356465

8-Port 10G Multi-Gigabit Switch

from **450,42 EUR**

Item no.: 356465
shipping weight: 2.20 kg
Manufacturer: TP-LINK



Product Description

- Eight 10 Gbps ports . 8 x 10 Gigabit ports provide the highest performance of your 10G / Multi-Gig bandwidth and devices, offering up to 160 Gbps switching capacity
- Lightning-fast connections . Provides lightning fast connections to 10G NAS, servers, 10G PCIe adapter / NIC, gaming computers, 2.5G / 5G / 10G WiFi 6 AP, 8K video and more
- Ideal for various scenarios . Designed for lightning fast connections in business and home offices, workstations, LAN parties and home entertainment
- Optimal 5-Gang Connections . Auto-negotiation of 5-speed connections (100 Mbps / 1G / 2.5G / 5G / 10G) provides optimal performance
- Quiet operation . Intelligent fan speed adjustment ensures minimal noise is not distracting during use
- Wide operating temperature . The robust metal housing and heat-dissipating design guarantee a wide operating temperature (0-50 ° C)
- Plug and Play . Enables easy deployment without the need for a technician

HARDWARE FEATURES

- Standards and protocols IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1p, 802.3an, 802.3bz
- Interface 8x 100 Mbit/s/1 Gbit/s/2.5 Gbit/s/5 Gbit/s/10 Gbit/s ports, auto-negotiation, auto-MDI/MDIX
- Number of fans 1 (intelligent adjustment of fan speed)
- External power supply 100-240 VAC, 50/60 Hz, 0.8 A
- LEDs
- System power: 1
- Link/Act indicators: 8, 1 indicator per port, integrated in each RJ-45 port
- Dimensions (W*D*H) 11.6 x 7.1 x 1.7 inches (294 x 180 x 44 mm)
- Maximum power consumption 31.2 W

POWER

- Switching capacity 160 Gbps
- Packet forwarding rate 119.0 Mpps
- MAC address table 32 K
- Packet buffer memory 2 MB
- Jumbo frames 10 KB

SOFTWARE FEATURES

- Advanced features: 802.3X flow control; 802.1p/DSCP QoS
- Transfer method Store and forward

OTHER

- Certification CE, FCC, RoHS
- Package contents: 8-port 10G multi-gigabit desktop/rackmount switch TL-SX1008; power cord; installation guide; rackmount kit; rubber feet
- Operating temperature: 0-50 °C (32-122 °F)
- Storage temperature: -40-70 °C (-40-158 °F)
- Operating humidity: 10-90 % relative humidity, non-condensing
- Storage humidity: 5-90 % relative humidity, non-condensing

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

