

Item no.: PR1500ELCD

## PR1500ELCD - Line-Interactive UPS 1500 VA / 1350 W, SNMP Slot

from **626,04 EUR**

Item no.: PR1500ELCD  
shipping weight: 27.60 kg  
Manufacturer: CyberPower



### Product Description

CyberPower PR1500ELCD - Line-Interactive UPS 1500 VA / 1350 W, SNMP Slot  
CyberPower PR Tower Series  
The Professional Tower Series UPS provides advanced level of power protection to servers, telecom equipments, VOIP, internet working hardware and other mission-critical applications. Featuring Pure Sine Wave output and Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, it allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The optional SNMP/HTTP Remote Management Capability enables remote management and control of the system through standard web browser.

- GreenPower UPS(TM) Technology
- Pure Sine Wave
- Line-Interactive UPS Topology
- Automatic Voltage Regulation (AVR)
- EMI, RFI, Surge and Lightning Spike Protection
- Auto-Restart/Auto-Charge
- Emergency Power-Off (EPO) Port
- Protected On/Off Switch
- Multifunction LCD Readout
- USB & Serial Connectivity Ports
- Hot-Swappable Battery Packs
- User-Replaceable Batteries
- SNMP/HTTP Remote Management Capability (Optional)
- PowerPanel Business Edition Software

#### Configuration

- Capacity (VA / Watts): 1500/1350
- Energy-Saving Technology: Yes

#### Input

- Frequency Range: 50/60 Hz +/- 3 Hz (Auto-sensing)
- Input Plug Type: IEC 320 C14

#### Output

- UPS Outlets (Numbers): (8) IEC
- On Battery Output Voltage: Pure Sine Wave at 230 Vac +/- 5 %
- On Battery Output Frequency: 50/60 Hz +/- 1 %
- Transfer Time (Typical): 4 ms
- Overload Protection: On utility: Internal Current Limiting & Circuit Breaker; On battery: Internal Current Limiting
- AVR Function: Double Boost, Single Buck

#### Surge Protection and Filtering

- Lightning / Surge Protection: Yes

#### Physical

- Dimensions (H x W x D) (mm): 221 x 170 x 432
- Weight (kg): 25.1

#### Battery

- Sealed Maintenance Free Lead Acid Battery: 12 V / 17 AH x 2
- User Replaceable: Yes
- Typical Recharge Time: Quick Charge: 3 Hours, ECO Mode: 8 Hours

#### Runtimes

- Half-load / Full-load (mins): 17 / 5

#### Status Indicators

- Indicators: Power On, Online, On Battery, Fault, Replace Battery
- Audible Alarms: On Battery, Low Battery, Overload
- Multi-function LCD Readout: Yes

#### Communication

- PowerPanel(R) Business Edition Software: Windows 8 / 7 / Vista / XP / 2000, Server 2012 / 2008 / 2003, Linux, VMware Esxi, and CitrixXenserver

#### Management

- Self Test: Yes
- Auto-Charge / Auto-Restart: Yes
- Connectivity Ports: USB, Serial
- SNMP/HTTP Capable: Option

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

