

Item no.: 365028

10? resistive touch monitor

from **276,54 EUR**

Item no.: 365028
shipping weight: 2.10 kg
Manufacturer: faytech



Product Description

faytech's 7-10? touch monitors feature numerous detail enhancements including lockable standard connectors, unique rear cable routing and mounting frames for machine and wall mount integration. In addition, each model has a faster start-up time and response time due to our improved controller chipset.

The series retains its rich assortment of features such as: LED backlight, 4-wire resistive touch panel, extra rugged components, extended power input (8-36V), VGA+HDMI connectors, three video inputs, wall mounting, a high quality stand and an extended temperature range. The high resolution support (e.g. 1080p, 1920x1200 pixels) of these faytech touch monitors makes them the perfect choice for a variety of applications.

For example, as a surveillance monitor in combination with an HTPC or with security cameras; as an operating panel in the industrial sector; in kiosk systems; as a cash register monitor or information terminal; for machine control; for home automation; for controlling wind turbines; for telematics in transport systems and in many other areas.

IP protection class

- IP 40

LCD panel

- Screen diagonal (inch/cm) 9.7" / 24.6 cm
- Active area display (cm) 19.70 cm x 14.70 cm (7.755 in x 5.787 in)
- Aspect ratio 4:3
- Physical resolution 1024x768 px
- Maximum displayable external resolution - HDMI, DP 1920x1080 px
- Brightness 350 (cd/m²)
- Contrast 800:1
- Typical response time Tr/Tf 10/15 (ms)
- Viewing angle h/v 170/170 (°)
- Backlight LED
- Lifetime backlight 20,000 hours

Touch Panel

- Touch Technology 4-Wire Resistive
- Available touch panel drivers Windows
- Linux
- Mac
- Android
- Touch lifetime 1 million touch in 1 location
- Surface hardness 3H
- Surface treatment Anti-glare

Operating notes

- Operating temperatures -25 °C ~ +75 °C (-13 °F ~ 167 °F)
- Humidity range (min/max) 10% - 90% RH
- Net weight 1.20 kg / 2.6455 lb
- Total weight (incl. packaging) 2.20 kg / 4.8501 lb
- Enclosure material Plastic
- Enclosure size 235.0 mm x 202.0 mm x 35.1 mm (9.251 in x 7.952 in x 1.381 in)

Power consumption

- Power indicator Green LED
- Power supply 100-240V ACDC active switching; 12V DC-Out
- Operating voltage 8-36 V
- Power consumption 8 W
- Standby power consumption 1 W

External connections

- Video 1x HDMI 1.3 (incl. HDCP)
- 1x VGA
- 1x Video1
- 1x Video2_Backview
- 1x Backview-Detect
- 1x YpbPr
- Audio chip 1x VGA audio, 1x video audio, 1x ear-out
- Touch connections 1x USB 1x Serial
- Other connections 1x 8-36V DC-In 1x USB (front)

Included in delivery

- Power supply unit (see power consumption)
- Quick start guide
- Stylus
- Remote control
- Cable (VGA, USB Touch)
- Car adapter
- AV Molex 2.5 Connector
- faytech FTV75PSF Stand
- Holding frame
- Holding rail
- Cable cover

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

