

Item no.: 365056

10" IP65 resistive touch monitor

from **446,51 EUR**

Item no.: 365056
shipping weight: 2.20 kg
Manufacturer: faytech



Product Description

faytech's 7"-15" IP65 high brightness touchscreen monitor series can be optimally used in even the harshest industrial and outdoor environments.

Advantages of these devices:

- Full IP65 protection (dust and waterproof)
- All-in-one cable solution, with VGA or HDMI video connection, USB for touch and an 8-36 V power supply

The housing of the unit is made of a robust, sealed aluminium casing, with two buttons on the front to adjust the brightness (with 5 available levels). On the back of the unit are mounting holes for VESA 75 or VESA 100 mounting, ensuring solid mounting in any environment.

IP protection class

- IP 65

LCD panel

- Screen diagonal (inch/cm) 9.7" / 24.6 cm
- Active area display (cm) 20.28 cm x 15.20 cm (7.984 in x 5.984 in)
- Aspect ratio 4:3
- Physical resolution 1024x768 px
- Maximum displayable external resolution - HDMI, DP 1920x1080 px
- Brightness 350 (cd/m²)
- Contrast 800:1
- Typical response time Tr/Tf 10/15 (ms)
- Viewing angle h/v 170/170 (°)
- Backlight LED
- Lifetime backlight 20,000 hours

Touch Panel

- Touch Technology 5-wire resistive
- Available touch panel drivers Windows
- Linux
- Mac
- Android
- Touch lifetime 10 million in 1 location without failure
- Surface hardness level 3H
- Surface treatment Anti-glare

Operating notes

- Operating temperatures -25 °C ~ +75 °C (-13 °F ~ 167 °F)
- Humidity range (min/max) 10% - 90% RH
- Net weight 1.80 kg / 3.9683 lb
- Total weight (incl. packaging) 2.50 kg / 5.5115 lb
- Enclosure material Aluminium
- Enclosure size 257.2 mm x 196.4 mm x 39.5 mm (10.12 in x 7.732 in x 1.555 in)

Power consumption

- Power indicator Green LED
- Power supply 100-240V ACDC active switching; 12V DC-Out
- Operating voltage 8-36 V
- Power consumption 8 W
- Standby power consumption 1 W

External connections

- All-in-one cable 1x HDMI, 1x USB-Touch, 1x 8-36V DC-In

Included in delivery

- Power supply (see power consumption)
- Quick start guide
- Stylus Stylus pen
- Remote control
- All-In-One cable - 2m length, attached to monitor (length customizable upon request)

Specifications

**Scan this QR code to
view the product**

All details, up-to-date
prices and availability

