

Item no.: 365063

FT19N3350W4G128G - 19" RES TPC N3350 4G 128GB SSD V4

from **1.169,57 EUR**

Item no.: 365063
shipping weight: 6.20 kg
Manufacturer: faytech



Product Description

The Resistive Touch PC series from faytech stands out from the competition with fanless, quiet operation and a robust aluminium housing with stable VESA 100 mounting bolts. The Touch PC is powered by faytech's industrial Apollo Lake mainboard. It is powered by the Intel® Celeron® N3350 DualCore processor with up to 2.40 GHz clock frequency. This version is equipped with 4 GB RAM (max. 8 GB), 128 GB SSD and Intel's HD graphics chipset and supports Full HD, DirectX 11.1 and OpenGL 4.0. These faytech PCs are the perfect choice for a variety of applications, including POS systems, control panels in industrial areas, in kiosk systems, office/home automation, digital signage and in areas such as shopping centres, classrooms, hotels and many more.

IP protection class- IP 40PC System- Processor/CPU: Intel® Pentium® QuadCore N3350- GPU Graphics: Intel® HD Graphics- Audio chip: Realtek ALC3251 Audio CODEC- Memory: 4 GB DDR4 non-ECC (max. 8 GB)- Removable storage: faytech Industrial 128 GB SSD- Network: 2x Realtek PCIe GB LAN 8111G (1x optional with POE); W-LAN- Driver support: Windows 10 + Linux Ubuntu- Pre-installed operating system (OS): Linux UbuntuLCD panel- Screen diagonal (inch/cm): 19 / 48.2 cm- Active display area (cm): 41.22 x 25.91 cm (16.22 in x 10.20 in)- Aspect ratio: 16:9- Physical resolution: 1440x900 px- Maximum displayable external resolution - HDMI, DP: 1920x1200 px- Brightness: 250 (cd/m²)- Contrast: 1000:1- Typical response time Tr/Tf: 1.5/3.5 (ms)- Viewing angle h/v: 170/160 (°)- Backlight: LED- Backlight lifetime: 30.000 hoursTouch panel- Touch technology: 5-wire resistive- Touch lifetime: 10 million at 1 point without error- Surface hardness: 3H- Surface treatment: Anti-glareOperating instructions- Operating temperatures: -10°C ~ +60°C (14°F ~ 140°F)- Humidity range (min/max): 10% - 90% RH- Net weight: 4.75 kg / 10.471 lb- Total weight (incl. packaging): 7.10 kg / 15.652 lb- Housing material: Aluminium- Housing size: 468.0 x 314.0 x 62.9 mm (18.42 in x 12.36 in x 2.476 in)Power consumption- Power indicator: Green LED- Power supply: 100-240 V ACDC active switching; 12 V DC-Out- Operating voltage: 12 V- Power consumption: 21 W- Standby power consumption: 1 WInternal connections- 1x SO-DIMM, max. 8 GB, DDR3L 1333/1600/1867 non-ECC, Single channel memory- 3x RS232/RS485 COM ports switchable in BIOS- 2x LCD backlight control/LCD panel power box- 1x 5 V/12 V SATA power connector- 1x 12 V DC power connector (2-pin)- 1x 4-pin SATA power connectorpin SATA power connector- 1x S/PDIF output pin header- 1x 8-bit digital I/O interface- 1x Line-out / Mic-in header- 1x Front panel box header- 1x Serial ATA 6 Gb/s- 1x MIPI CSI connector- 1x LVDS connector- 2x USB 3.0 box headerExternal connections- 1x 12 V DC-In (screwable)- 1x 12 V 3-Pin DC-In (screwable)- 1x W-LAN antenna connector (RP-SMA male)- 2x USB 2.0- 2x USB 3.0- 1x HDMI- 1x DP- 1x MIC-In & EAR-Out- 2x COM port Full-PIN - RS232/485; 5 V/12 V- 2x 10/100/1000Mbit RJ45 ports- 1x 2.5" module slot, changeable SSD includedExpansion slots- 1x mSATA full size (occupied by SSD)- 1x M.2 E-Key slot (occupied by WiFi card)- 1x SATA connector- 1x External PCIe x1 straddle connectorIncluded in delivery- Power supply unit (see power consumption)- Quick start guide- W-LAN antenna (RP-SMA female)

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

