

Item no.: 361359

3.5" SuperSpeed USB Card Reader 6 slots + 1 x USB Type-A socket

from **22,18 EUR**

Item no.: 361359
shipping weight: 0.20 kg
Manufacturer: Delock



Product Description

This card reader from Delock is designed for installation in a 3.5" slot of the PC and is connected to an internal USB connector. It has six different card reader slots and enables the connection of a USB device.

Specification

- Connections:
- external:
- 1 x CF slot
- 1 x SD slot
- 1 x Micro SD slot
- 1 x xD slot
- 1 x MS slot
- 1 x M2 slot
- 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A socket
- internal:
- 1 x 19-pin SuperSpeed USB (USB 3.2 Gen 1) pin socket
- Data transfer rate up to 5 Gbps
- 1 x LED indicator
- Metal housing for installation in 3.5" slot
- Cable length: approx. 50 cm
- Hot swap, plug & play

Supports the following memory cards:

- Slot 1
- CF I, CF II, CF4.0, CF Ultra, CF Ultra DMA, CF Ultra II, CF Ultra III, CF Ultra IV,
- CF Extreme, CF Extreme III, CF Extreme IV
- Slot 2
- SD, SD Pro, SD Ultra, SD High Capacity (SDHC), Turbo SD, SDHC Turbo,
- SD Ultra, SD Ultra II, SDHC Ultra, SDXC, SDXC Ultra, MMC-I, MMC-II,
- MMC plus, MMC plus Turbo, MMC 4.0, Mini SD, Mini SDHC, Turbo Mini SD,
- MMCmobile, RS-MMC, RS-MMC 4.0
- Slot 3
- MicroSD, Micro SDHC, Micro SDXC
- Slot 4
- xD
- Slot 5
- MS, High Speed Memory Stick (HS-MS), MS Pro, MS Pro-HG, MS-HG,
- Memory Stick XC, MS Magic Gate, MS-Pro Magic Gate, MS-Duo,
- MS-Duo Magic Gate, MS-Pro Duo, MS Pro-HG Duo, MS-Duo, MS XC-Duo,
- MS XC-HG Duo
- Slot 6
- M2

System requirements

- Linux Kernel 5.8 or higher
- Windows 8.1/8.1-64/10/10-64
- PC with a free 3.5" slot
- Mainboard with a free 19 pin SuperSpeed USB (USB 3.2 Gen 1) header connector

Package contents

- 3.5" Card Reader with connection cable
- Screws
- Instruction manual

Packaging

- Retail Box

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

