

Item no.: 361252

USB 2.0 adapter to 4 x serial RS-422/485

from **93,39 EUR**

Item no.: 361252
shipping weight: 0.40 kg
Manufacturer: Delock



Product Description

With this adapter from Delock, up to four serial devices can be connected via a USB type-A port.

Specification

- Connectors: 1x USB 2.0 type-B socket > 4x serial RS-422/485 DB9 plug, 1x 5 V DC power socket
- Chipset: FT4232HL, SP3078EE
- 4 x DIP switches: RS-422/485 mode setting
- Internal pin connectors: jumpers switch terminators on / off
- Serial connector with nuts
- Data transfer rate up to 1 Mbps
- LEDs to indicate TxD / RxD activity
- Automatic detection and switching between RS-422 and RS-485
- ±15 kV ESD protection on all signal pins
- Wall bracket integrated in the housing
- Power consumption Operation: ? 143 mA / 715 mW
- Standby: approx. 92 mA / 460 mW
- Additional I/O and IRQ are not required
- DC connection for optional power supply unit
- Operating temperature: 0 °C ~ 70 °C
- Dimensions (LxWxH): approx. 172 x 65 x 23 mm

Specification of power connection

- 5 V, ground outside, plus inside
- Dimensions inside: ø approx. 2.1 mm, outside: ø approx. 5.5 mm
- Length: approx. 9.5 mm

System requirements

- Linux Kernel 2.6 or higher
- Windows Server 2012/Server 2012 R2/Server 2016
- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC or notebook with a free USB type-A port

Package contents

- USB 2.0 to 4 x Serial RS-422/485 adapter
- USB 2.0 cable
- 8 x jumpers
- Driver CD
- Instruction manual

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

