

Item no.: 323550

AWPCI36T - 802.11g 54 Mbps PCI Adapter

from **15,77 EUR**

Item no.: 323550
shipping weight: 0.30 kg
Manufacturer: ALFA Network



Product Description

ALFA AWPCI36t - 802.11g 54 Mbps PCI Adapter

The AWPCI36t is PCI adapter with an external detachable dipole antenna. Features

- Complies with IEEE 802.11b/g wireless standard
 - Complies with PCI revision 2.2 and PCI power management revision 1.1
 - Dynamic data rate scaling at 1, 2, 5.5 and 11 Mbps for 802.11b and 6, 9, 12, 18, 24, 36, 48 and 54 Mbps for 802.11g
 - High-speed transfer data rate up to 54 Mbps
 - Supports turbo mode for 72 Mbps data rate
 - Supports wireless data encryption with 64/128-bit WEP, WPA (TKIP with IEEE 802.1x) and AES functions
 - Range coverage: Indoor 35~100 meters; outdoor 100~300 meters
 - Supports Wake-on-LAN (WOL) function and remote wake-up
 - Equips one external detachable dipole antenna
 - Support driver for Windows 98se, Me, 2000 and XP
 - Compliant with FCC Part 15.247 for US, ETS 300, 328 for Europe
 - Supports auto-installation and diagnostic utilities
-
- Standards: IEEE 802.11g, IEEE 802.11b
 - Security: 64/128-bit WEP, WPA (TKIP with IEEE 802.1x), AES
 - Receiver sensitivity: 54 Mbps OFDM, 10% PER, -68 dBm; 11 Mbps CCK, 8% PER, -86 dBm; 1 Mbps BPSK, 8% PER, -92 dBm
 - Channels: USA 11, Europe 13, Japan 14
 - Data rates: 802.11b: 1, 2, 5.5 and 11 Mbps; 802.11g: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps
 - Transmit power: 16 ~ 18 dBm
 - Range coverage: Indoor 35~100 meters; outdoor 100~300 meters
 - Operating temperature: 0°C to 40°C (32°F to 104°C)
 - Operating humidity: 10% ~ 90% (non-condensing)
 - Emission: FCC Class B, CE Mark, VCCI Class B

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

