

Item no.: 356936

GSM Activate 4G Door Contact Alarm

from 168,62 EUR

Item no.: 356936 shipping weight: 0.60 kg Manufacturer: GSM Activate



Product Description

Our GSM Door Contact Alarm system is a standalone alarm system. It is ideal for smaller rooms inside properties. By using GSM technology, when the door contact is broken the unit will send the user a text message and/or phone call to the users mobile phone or landline. Therefore, providing the occupier of the room instant notification when the room has been breached. The unit is housed in a perfectly weathered box enabling the unit to be installed outside as well as inside. Furthermore, the unit has been tested in high temperatures as well as freezing temperatures. Customers with questions regarding the product can contact us on the above numbers for more information.

GSM Module Specification- GSM Frequency: Quadband freq 850/900/1800/1900/ 3G Model 2100Mhz- Power Supply Voltage: 9 – 24 volts DC – 1 Amp Min- Current used in standby mode: 60mA Max- IP65 rated enclosure for outside installation- Micro 2G or 3G Simcard- No landline required- Dimensions: L100 x W68 x H50mm- Dimensions PCB Only: L95 x W67mm- Sim Active Function- Operating Temperature: -10...+40°C- Programmed by text message- Text to test signal strength- Key Fob Arming / DisarmingPIR Specification- Alert Distance: 25 – 35mm seperation- Detection: Dual function, magnetic door and emergency switch- Battery Life: 6 months- Dimensions: L60 x W32 x H13mm-Wireless range: 25 feet

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

