

Item no.: 331226

## BPI-MT7615 - Banana Pi 4)

from **18,02 EUR**

Item no.: 331226  
shipping weight: 0.10 kg  
Manufacturer: BPI



### Product Description

Banana Pi BPI-MT7615 (for BPI-R2/ BPI-R64)

The MT7615 is a highly integrated Wi-Fi single chip which support 1733 Mbps PHY rate. It fully complies with IEEE 802.11ac and IEEE802.11 a/b/n standards, offering feature-rich wireless connectivity at high standards and delivering reliable, cost-effective throughput from and extended distance. Optimized RF architecture and baseband algorithms provide excellent performance and low power consumption. Intelligent MAC design deploys a high efficient offload engine and hardware data processing accelerators which completely offloads Wi-Fi task of the host processor.

The MT7615 is designed to support standard based features in the areas of the host processor and in the areas of security quality of service and international regulations. This giving end users the greatest performance any time and in any circumstance. Furthermore, it supports concurrent dual-band operation at 5 GHz and 2.4 GHz band (DBDC, Dual-Band-Dual-Concurrent0). This enables diversified applications that require one link at 2.4 GHz band and the other at less crowded 5 GHz band simultaneously. Additionally, the MT7615 supports MU-MIMO with different configurations. As an AP it would be able to use its antenna beams to transmit multiple frames to different clients simultaneously and over the same frequency spectrum.

Supported Operation Systems:

- Linux
- OpenWRT
- Android
- Support 4x4 4SS 11ac wave2 MU-MIMO and 160 MHz channels
- Mu-MIMO configurations of: 4x users: 4x 1 SS/ 3x users: 2x 1 SS + 1x 2 SS or 3x 1 SS/ 2x users: 2x 2 SS or 1x 1 SS + 1x 2 SS or 2x 1 SS
- Support 5, 10, 20, 40, 80, 80+80 and 160 MHz channels
- Embedded ARM cortex R4 processor for full host CPU offload
- Embedded 32-bit RISC microprocessor
- iNIC Gen2 with full Wi-Fi offload
- Highly integrated RF with 40 nm low power process
- 4T4R with support of up to 1733 Mbps PHY rate
- Configurable 4x4/3x3 or 2x2n+2x2ac DBDC
- Noise mitigation: Supports background scan function for fast channel switching; Supports spectrum analysis for non-Wi-Fi signals
- Intelligent power saving
- Hardware-based airtime fairness (QoS)
- Integrate high efficiency internal 2.4G/ 5G PAs
- Intelligent Calibration (iCal) reduces the production time
- Supports external PA/LNA/TRSW design
- WoWLAN via GPIO (client mode), supports host sleep (AP mode)
- Compact 12 mm x 12 mm DRQFN118 package with PCIe Gen2 interface

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



