

Item no.: 341098

## PR3PDNP0 - DIN Rail Power Supply

from **17,05 EUR**

Item no.: 341098  
shipping weight: 0.20 kg  
Manufacturer: Teltonika



### Product Description

PR3PDNP0 - DIN Rail Power Supply

Power supply for rail mounting from Teltonika.

- Single output power: 20 W
- Input voltage range: 100-240 VAC 50/60 Hz
- DC output voltage: 12 V
- DC output current: 0~1.67 A
- Output ripple and noise: 120 mVp-p
- Line regulation: +/-1 %
- Load regulation: +/-1 %
- Efficiency: 80 %
- Adjustable range for DC voltage: +/-1 %
- Test standard: EN60950-1: 2006+A11: 2009+A1: 2010+A12: 2011+A2: 2013; EN55022: 2010; EN61000-3-2: 2014; EN61000-3-3: 2013; EN55024: 2010/A1: 2015
- Inrush current: Cold start current 20 A/115 VAC; 40 A/230 VAC
- Overload protection: 105% ~ 160% cut off the output, automatic recovery
- Over voltage protection: 120% ~ 140% shut down O/P voltage, re-power on to recover
- Setup, rise, hold up time: 500 ms; 30 ms/230 V AC at full load; 1000 ms; 30 ms/115 VAC at full load
- Withstand voltage: I/P-O/P: 1.5 kV; I/P-FG: 1.5 kV; O/P-FG: 0.5 kV 1 minute
- Isolation resistance: I/P-O/P I/P-FG O/P-FG: 500 V DC/1000 Mohms
- Working temperature: -10°C ~ +50°C
- Mounting options: 35 mm DIN rail
- Dimensions: 22.5 x 90 x 100 mm
- Weight: 19 g

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

