

Item no.: 373782

## 90586 - Industrial barcode scanner 1D & 2D, 433 MHz or Bluetooth, inductive charging station

from **207,41 EUR**

Item no.: 373782  
shipping weight: 0.80 kg  
Manufacturer: Delock



### Product Description

This barcode scanner by Delock can be connected wirelessly to a PC, notebook or directly to a mobile phone or tablet. All common 1D and 2D barcode types can be scanned precisely, even at long distances. The scanner also recognises barcodes shown on displays and monitors. Automatic adaptation to ambient brightness: The scanner automatically adapts to the ambient brightness and captures up to 120 scans per second under optimum lighting conditions. In low ambient light, the barcode is illuminated by an additional white LED and can therefore also be used in poor lighting conditions. Robust workmanship: Thanks to its robust workmanship, the scanner can withstand drops of up to 1.80 m and is therefore ideal for use in industrial environments. Charging station acts as an interface: The scanned barcodes are transmitted either via Bluetooth or via the 433 MHz frequency band. In addition to charging the hand-held scanner, the inductive charging station also functions as a 433 MHz interface and is connected to the system via USB cable. Note: Not suitable for Swiss QR codes.

Specification charging station- Connection: 1 x USB 2.0 type A plug- Input voltage: 5 V- Power consumption: operation max. 1100 mA, standby max. 700 mA- Operating temperature: -20 °C ~ 50 °C- Storage temperature: -40 °C ~ 70 °C- Relative humidity: 5 - 95 % (non-condensing)- Colour: black- Weight: approx. 295 g- Dimensions (LxWxH): approx. 180 x 100 x 75 mm- Cable length without connections: approx. 1.25 m- Bluetooth Standard V 4.1- 433 MHz Specification Barcode Scanner- Decoding chip: ARM Cortex 32 Bit- Battery: Li-Polymer 1800 mAh- Resolution: max. 1280 x 800- Trigger: Push button- Read distance: approx. 30 mm to 500 mm- Reading accuracy: 3 - 4 mil- Range: Bluetooth up to 10 m, 433 MHz up to 100 m- Internal memory: 16 MB- Scan type: LED- Light colour: visible LED red- Compensation light: LED white- Sensor: CMOS image sensor- Scan rate: up to 120 scans per second- Scan angle: 55°- Ambient brightness: max. 100000 Lux- Input voltage: 5 V- Current consumption: operation max. 220 mA, standby max. 20 mA- Operating temperature: -20 °C ~ 50 °C- Storage temperature: -40 °C ~ 70 °C- Relative humidity: 5 - 95 % (non-condensing)- Colour: black / yellow- Weight: approx. 321 g- Dimensions (LxWxH): approx. 185 x 100 x 80 mm- Scan codes: Code 128, Code 39, Interleaved 2 of 5, EAN-8 / EAN-13, ISBN - 13, Data Matrix, Micro, PDF417, Micro QR, PDF417, QR Code System requirements- Android 11.0 or higher- Bluetooth Standard 4.1 or higher- iPad Pro (3. generation) or higher- Mac OS 11.6 or higher- Windows 8.1/8.1-64/10/10-64/11- PC or notebook with a free USB Type-A port for dongle Package contents- Barcode scanner- Charging cradle- Operating instructions

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

