

Item no.: CRS504-4XQ-IN

## CRS504-4XQ-IN - Cloud Router Switch, 4x 100 Gigabit QSFP28 ports

from **692,44 EUR**

Item no.: CRS504-4XQ-IN  
shipping weight: 2.50 kg  
Manufacturer: MikroTik



### Product Description

CRS504-4XQ-IN - Cloud Router Switch, 4x 100 Gigabit QSFP28 ports

MikroTik's 100 Gigabit family keeps expanding – you've already seen the incredible CCR2216 100 Gigabit router. Now it's time for a matching switch – the CRS504-4XQ-IN. The small size combined with the low power consumption (25 W without attachments!) is perfect to start expanding 100 Gigabit networking in everyday setups. This speed is no longer limited to data centers, ISPs, and large offices. You too can upgrade your 10 or 25 Gigabit network and join the one hundred club!

There are four 100 Gigabit QSFP28 ports. Use them to connect other 100 Gigabit devices or grab a breakout cable to connect multiple 25 Gigabit devices: each port is connected to four 25 Gigabit lines, allowing you to connect 16x 25 Gigabit devices. In fact, you can mix and match all kinds of connections this way: 100 Gigabits on one port, 40 Gigabits on the other, 4x 25 Gigabits on the third, and maybe even some 10G or 1G cables on the fourth. The mighty Marvell DX4310 switch-chip will handle everything without breaking a sweat! Obviously, there is an Ethernet port for management purposes as well.

MikroTik has been using this switch for quite some time now in the Genomics Data Network project. A high-capacity data network for their local scientists working on ground-breaking cancer treatments. Genome data can take up a lot of space, so you need exceptionally fast connections there. Also, with these devices, Latvia became the first Baltic country to establish a 100 Gigabit connection to the pan-European research network.

With multiple powering options and the ability to be mounted on the wall, this switch will make any system administrator happy.

Included parts

- Rack ears (CRS504)
- K10 screw kit
- 2x IEC cords

Specifications

- Product code: CRS504-4XQ-IN
- CPU: QCA9531 650 MHz
- CPU architecture: MIPSBE
- CPU core count: 1
- Size of RAM: 64 MB
- Storage: 16 MB, Flash
- Number of 100 Mbit Ethernet ports: 1
- Number of 100G QSFP28 ports: 4
- Switch chip model: 98DX4310
- Dimensions: 320 x 185 x 44 mm
- Operating system: RouterOS v7, License level 5
- Operating temperature: -40°C to +70°C

Powering

- Number of DC inputs: 3 (PoE-in, DC jack, 2-pin terminal)
- PoE-in input voltage: 43-57 V passive PoE or 802.3bt Class 6
- DC jack input voltage: 36-57 V
- 2-pin terminal input voltage: 36-57 V
- Max. power consumption without attachments: 25 W
- Max. power consumption: 41 W

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

