

Item no.: 373792

47235 - 5.25" removable frame for 4 x 2.5" U.2 NVMe SSD with lockable trays

from **237,18 EUR**

Item no.: 373792
shipping weight: 0.90 kg
Manufacturer: Delock



Product Description

This solid metal removable frame by Delock is suitable for installation in a free 5.25" bay of a PC, IPC or server case and allows the operation of up to four 2.5" U.2 SSDs. To ensure maximum speed at each connection, each slot has its own SFF-8643 connection. Quick replacement of the SSDs The special mechanism allows the SSDs to be replaced quickly and easily. For example, data backups can be removed and stored in a safe place. Protection against theft Each of the four removable frames is equipped with a separate lock. This protects the hard drives and data from theft and misuse. Well cooled During operation, two 35 mm fans at the rear provide an efficient and effective airflow to cool all 4 slots. The fans can be set to either slow or fast speed to ensure optimum cooling.

Specification- Internal connections: 4 x SFF-8639 socket- External connections: 4 x Mini SAS HD SFF-8643 socket, 1 x SATA 15 pin power connector- Suitable for 2.5" U.2 NVMe SSD: SSD height up to 15 mm- Compatible with PCI Express V4.0- Removable frame with key lock for each bay- 4 x LED display for power and access- Robust aluminium housing- 2 x fans 35 x 35 mm on the rear- Fan speed adjustable in 2 steps- Key lock- Bootable- Operating temperature: 0 °C ~ 55 °C- Storage temperature: -20 °C ~ 55 °C- Relative humidity: 5 - 65 % (non-condensing)- Dimensions (LxWxH): approx. 146 x 139 x 42 mm System requirements- Linux Kernel 5.1 or higher- Windows 8.1/8.1-64/10/10-64- Windows Server 2016- One free 5.25" bay- Up to four free U.2 ports- Power supply with one free SATA power connector Package contents- 5.25" removable frame- 4 x 2.5" removable frame slot- 2 x keys- 8 x frame screws- 16 x hard drive screws- User manual

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

