

Item no.: 373510

62704 - 3.5" converter SATA 22 Pin / SFF-8643 NVMe > 1 x M.2 Key M + 1 x M.2 Key

from **87,69 EUR**

Item no.: 373510
shipping weight: 0.20 kg
Manufacturer: Delock



Product Description

An M.2 SSD in 2280, 2260, 2242 and 2230 format with Key B and an M.2 SSD in 2280, 2260, 2242 and 2230 format with Key M can be connected to this Delock converter. It enables the use of an M.2 SSD on PCIe and an M.2 SSD SATA basis at the same time. The converter can be integrated into the system internally via the SATA interface when using a SATA M.2 SSD, or via the SFF-8643 interface when using a PCIe M.2 SSD.

Specification- Connectors for SATA SSDs: 1 x SATA 6 Gb/s 22 pin plug- Connectors for PCIe SSDs 2 or 4 lanes: 1 x 36 pin SFF-8643 socket- Connectors for PCIe SSD: 1 x 67 pin M.2 Key M slot- Connectors for SATA SSD: 1 x 67 pin M.2 Key B slot- Interface: SATA / PCIe (2 or 4 lanes)- Suitable for M.2 modules in the format: 2280, 2260, 2242 and 2230 with Key M or Key B+M on PCIe basis or SATA basis- Maximum height of the components on the module: 1.5 mm,- Use of double-sided modules possible- SATA 15 pin power connector always required- LEDs for power and activity- Supports NVM Express (NVMe)- Maximum output current: 4 A (PCIe) and 3 A (SATA)System requirements- Linux Kernel 3.16 or higher- Windows 7/7-64/8.1/8.1-64/10/10-64/11- One free SATA 22 pin interface- One free SFF-8643 interface (PCIe SSD)Package contents- 3.5" converter- Mounting material- User manual

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

