

Item no.: SC-2402-0213-5354

ES-8-150W-EU - Managed PoE+ Gigabit Switch with SFP

180,35 EUR

Item no.: SC-2402-0213-5354

shipping weight: 2.30 kg

Manufacturer: Ubiquiti



Product Description

ES-8-150W - Managed PoE+ Gigabit Switch with SFP

- Non-Blocking Throughput Switching Performance
- Gigabit Ethernet RJ45 and SFP+/SFP Ports
- Auto-Sensing IEEE 802.3af/at PoE

Build and expand your network with EdgeSwitch(TM), part of the EdgeMAX line of products. The EdgeSwitch is a fully managed, PoE+ Gigabit switch, delivering robust performance and intelligent switching for growing networks. The EdgeSwitch offers an extensive suite of advanced Layer-2 switching features and protocols, and also provides Layer-3 routing capability. [Switching Performance](#) The EdgeSwitch offers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss. The EdgeSwitch provides total, non-blocking throughput:

- 8-Port Model: Up to 10 Gbps

[PoE+ Flexibility](#) The EdgeSwitch models are available with 8, 16, 24, or 48 PoE Gigabit Ethernet ports of auto-sensing IEEE 802.3af/at or configurable 24V Passive PoE to simplify your infrastructure. By default, the EdgeSwitch automatically detects 802.3af/at devices so they automatically receive PoE. For 24V Passive PoE devices, manually enable 24V passive PoE using the EdgeSwitch Configuration Interface. [Fiber Connectivity](#) The EdgeSwitch provides fiber connectivity options for your growing networks. The 8, 16, and 24-port models include two SFP ports, providing up to 1 Gbps uplinks. For high-capacity uplinks, the 48-port models include two SFP and two SFP+ ports, providing uplinks of up to 10 Gbps.

Modell: ES-8-150W

- (8) Gigabit RJ45-Ports
- (2) SFP-Ports
- (1) serieller Konsolen-Port
- Nicht blockierender Durchsatz: 10 Gbps
- Switching-Kapazität: 20 Gbps
- Forwarding-Rate: 14.88 Mpps
- Max. Stromverbrauch: 150 W
- Unterstützt PoE+ IEEE 802.3af/at und 24V Passive PoE
- Wandmontage mittels Montagehalterungen (inklusive)
- Desktop-Montage (stapeln Sie das Gerät NICHT)
- DC-Eingangsoption (redundant oder stand-alone)

[Hardware-Spezifikationen](#)

- Maße: 204 x 43 x 235 mm (8.03 x 1.69 x 9.25")
- Gewicht:
 - Ohne Montagehalterungen: 1.72 kg (3.79 lb.)
 - Inklusiv Montagehalterungen: 1.8 kg (3.96 lb.)
- Nicht blockierender Gesamtdurchsatz: 10 Gbps
- Switching-Kapazität: 20 Gbps
- Forwarding-Rate: 14.88 Mpps
- Max. Stromverbrauch:
 - Inklusiv PoE-Ausgang: 150 W
 - Ohne PoE-Ausgang: 20 W
- Stromversorgungsmethode:
 - AC: 100-240 V AC/50-60 Hz, integriertes AC/DC-Netzteil, Universaleingang
 - DC: 42 bis 56 V DC extern, (Polaritätsschutz) Klemmleisteingang
- Stromversorgung: AC/DC, intern, 150 W DC
- LEDs pro Port:
 - RJ45-Datenports: PoE, Geschwindigkeit/Verbindung/Aktivität
 - SFP-Datenports: Geschwindigkeit/Verbindung/Aktivität
- Netzwerkschnittstellen:
 - (8) 10/100/1000 Mbps RJ45 Ethernet-Ports
 - (2) 1 Gbps SFP Ethernet-Ports
- Steuerungsschnittstelle: (1) serieller RJ45-Port, Ethernet In/Out Band
- Zulassungen: CE, FCC, IC
- Wandmontage: Ja
- ESD/EMP-Schutz:
 - Luft: +/-24 kV
 - Kontakt: +/-24 kV
- Betriebstemperatur:
 - Interner AC/DC (at) 150 W: -25° C bis 45° C (-13° F bis 113° F)
 - Interner AC/DC (at) 100 W: -25° C bis 55° C (-13° F bis 131° F)
 - Externer DC: -25° C bis 60° C (-13° F bis 140° F)
- Feuchtigkeit: 5 bis 95% nicht kondensierend
- Schock und Vibrationen: ETSI300-019-1.4

Specifications

**Scan this QR code to
view the product**

All details, up-to-date
prices and availability

