

Item no.: 382922

42022 - External enclosure USB 20 Gbps for 2 x M.2 NVMe PCle SSD with USB Type-C Buc

127,^{50 EUR}

Item no.: 382922 shipping weight: 0.30 kg Manufacturer: Delock



Product Description

This aluminium enclosure by Delock allows the installation of two M.2 PCIe NVMe SSDs in 2280, 2260, 2242 and 2230 format. It can be connected to a PC or notebook via USB. The robust metal housing with cooling fins ensures an optimum storage temperature.M.2 PCIe SSD RAIDIf two SSDs are installed, it is possible to use different RAID modes.SSD installation without toolsThe special feature of this housing is that no tools are required to install the M.2 SSD. The cover can be pushed backwards with a little pressure, the SSD is attached to the board with a rubber nipple and then the cover is pushed back on until it clicks into place.

attached to the board with a rubber nipple and then the cover is pushed back on until it clicks into place.

Specification- Connections:external: 1 x USB 20 Gbps USB Type-CTM socket1 x USB Type-CTM socket (5 V power supply)internal: 2 x M.2 Key M Slot- Chipset: JMicron JMS586R-Supports M.2 modules in 2280, 2260, 2242 and 2230 format with Key M or Key B+M on PCle (NVMe) basis- Maximum height of the components on the module: 1.5 mm, use of double-sided modules possible- Supports NVM Express (NVMe)- Supports S.M.A.R.T.- Supports UASP- Data transfer rate up to 20 Gbps- 1 x power button- 1 x reset button- DIP switch for RAID mode- Supports RAID 0, RAID 1, JBOD, Port Multiplier- 7 x LED display- Hot Plug, Plug & Play- Bootable- Metal housing- Colour: black- Dimensions (LxWxH): approx. 120 x 68 x 17 mmPower supply specification- Plug-in power supply- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A- Output: 5.0 V / 3.0 A / 15.0 W System requirements- Android 11.0 or higher- Chrome OS- Linux Kernel 5.15 or higher- Mac OS 13.1 or higher- Windows 10/10-64/11- iPad Air (4th generation) or higher- iPad Pro (3rd generation) or higher-Surface Pro 7- Device with a free USB Type-CTM port or with a free ThunderboltTM 3 or ThunderboltTM 4 portPackage contents- External housing- Cable USB-CTM plug to USB-CTM plug, length approx. 45 cm- External power supply- 2 x heat conduction pads- 2 x heat conduction plates- 4 x use the conduction plates- 4

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

