

Item no.: 381852

TAT240R6BP01 - TAT240

from **88,71 EUR**

Item no.: 381852
shipping weight: 0.20 kg
Manufacturer: Teltonika



Product Description

Tamper-proof asset tracker with 4G LTE Cat 1 connectivity. Define your own data sending frequency based on whether your assets are moving. Attach the device firmly and effortlessly with the included magnetic mounting holder. Ideal to be used as a backup tracker – easy to hide anywhere in a vehicle thanks to a compact size, while sleep mode protects against detecting tracker by thieves.

SpecificationModule- Name: TAT240-QJIB0: Quectel EG915U-EU with Teltonika TM2500;TAT240-QKIB0: Quectel EG915U-LA with Teltonika TM2500- Technology : LTE Cat 1/GSM/GPRS/GNSS/BLUETOOTHGNSS- GNSS: GPS, GLONASS, GALILEO, BEIDOU- Receiver: 33 channel- Tracking sensitivity: -165 dBm- Position Accuracy: < 2.5 m
CECellular- Technology: LTE Cat 1, GSM- 2G bands:TAT240-QJIB0: EG915U-EU GSM: B2/B3/B5/B8;TAT240-QKIB0: EG915U-LA GSM: B2/B3/B5/B8- 4G LTE Cat 1 bands:TAT240-QJIB0: EG915U-EU LTE-FDD: B1/B3/B5/B7/B8/B20/B28;TAT240-QKIB0: EG915U-LA LTE-FDD: B2/B3/B4/B5/B7/B8/B28/B66- Data transfer:LTE: LTE FDD : Max 10Mbps (DL)/Max 5Mbps (UL)GSM: GPRS: Max 85.6Kbps (DL)/Max 85.6Kbps (UL)- Data transfer:LTE: LTE FDD : Max 10Mbps (DL)/Max 5Mbps (UL)GSM: GPRS: Max 85.6Kbps (DL)/Max 85.6Kbps (UL)- Data support:SMS (text/data)Power- Internal battery: Extremely low self-discharge Li-SOCI2 swappable, non-rechargeable battery, 7,2V 2200mAhBluetooth- Specification: 4.2 + LE- Supported peripherals: EYE sensors, Beacons, Universal BLE sensor supportPhysical specification- Dimensions:78 x 63 x 28 mm (L x W x H)- Weight:115 g (when 2 cell batteries are used)Magnetic holder specifications- Dimensions:77,5 x 61,5 x 27,5 mm- Material: PC + ABS- Operating temperature: -40 °C to +80 °C- Flame Classifications UL94: V-0- Magnets: 4 x Neodymium magnets, 20 x 7 mm, strength: min. 11 kg, nickel-plated, max. operating temp. +80 °CInterface- GNSS antenna: Internal High Gain- Cellular antenna: Internal GSM High Gain- USB: 2.0 Micro-USB- LED indication: 1 status LED light- SIM: Micro-SIM- Memory: 128MB internal flash memoryOperating environment- Operating temperature (without battery): -20 °C to +60 °C- Battery discharge temperature: -60 °C to +85 °C - Battery storage temperature: Recommended max 30°C- Ingress Protection Rating: IP68Features- Scenarios:Tamper detection, Accelerometer wake up, GNSS, Bluetooth sensor support, Recovery mode, Periodic tracking on stop / on move, Scheduler with time zones, Backup tracking, Static navigation, Lost BLE sensor- Sensors: Accelerometer- Sleep modes: Single custom sleep mode- Configuration and firmware update: FOTA Web, Teltonika Configurator (USB)- SMS: Configuration, Events, Debug- GPRS commands: Configuration, Debug- Time Synchronization: GNSS, NITZ, NTP

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

