

Item no.: 375111

N2QF - WiFi 4 2.4 GHz AP/CPE outdoor board, without antenna, 2 N sockets, mini PCIe, PoE, miniUSB

from **76,40 EUR**

Item no.: 375111
shipping weight: 0.40 kg
Manufacturer: ALFA Network



Product Description

External N-antenna connector NOT included Various antenna options External antenna connector offers more choice for different applications PoE Out to power another N2QF No additional Ethernet cable required to power another N2Q or a passive PoE 24V device. Simply use another LAN port to generate 24 VDC and enable pass-through via the firmware. Make sure the connected device supports passive PoE 24VDC input before enabling pass-through via firmware Recommend a related product: DDC-2412 DDC-2412 works with N2Q to power 12VDC outdoor IP camera models, no additional power cable required

Features- High speed data rates- 802.11n 300 Mbps- Open source compatible- OpenWrt supported- Hardware watchdog- Ensuring proper operation- PoE pass-through software controllable- Software control PoE pass-through to ensure other devices are not accidentally damaged- Built-in mini USB port- With mini USB port could enrich function, such as 4G USB modem, web camera, etc. - With mini USB port could enrich function. such as 4G USB modem, web camera, WiFi USB antenna, etc.- Support channel width - Support channel width IP55 - Improved ESD protection Support channel width- Support channel width 5/10/20/40 MHz- Weatherproof design- IP protection class IP55- ESD protection- Improved ESD protection for LAN and RFSpecifications- Chipset: QCA9531- Standard: IEEE 802.11 n/g/b- Frequency: 2.4 GHz- Flash/SDRAM: 16 MB/ 128 MB- Ethernet speed: 10/100 Mbps- Interface: 2x LAN 1x reset button 1x mini USB 1x mini PCIe slot- Channel width: 5 / 10/ 20 / 40 MHz- Data rate: Up to 300 Mbps- Power requirement: 12V - 24V Passive PoE- Operating temperature: -30°C~ 60°C- Storage humidity: 10% ~ 90% (non-condensing)- Dimensions (mm): 300 x 80 x 30 mm- Weight: 0.4 kg RF specifications [Tolerance ± 2dB] Data rate (TX -RX)- MCS15: 23 -73- MCS14: 24 -77- MCS13: 26 -78- MCS12: 28 -83- MCS11: 29 -86- MCS10: 29 -89- MCS9: 29 -92- MCS8: 29 -94- MCS7: 23 -73- MCS6: 24 -76- MCS5: 26 -82- MCS4: 28 -85- MCS3: 29 -89- MCS2: 29 -91- MCS1: 29 -94- MCS0: 29 -95- 11g 54M: 25 -74- 11b 1M: 29 -96 Packaging contents- N2QF- Passive 24V PoE- PoE Pass through- N socket x2

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

