

Item no.: 383732

## FTC11XG - , Smart 10G SFP+ to 10G Ethernet Fiber to Copper converter

from **121,30 EUR**

Item no.: 383732  
shipping weight: 1,30 kg  
Manufacturer: MikroTik



### Product Description

A weatherproof IP55 Fiber-to-Copper converter to transform your 10 Gigabit SFP+ fiber connections into RJ45 10 Gigabit Ethernet. FTC11XG offers low power consumption (9-10 W) and two ways of powering: a standard DC jack & 802.3 af/at/bt 43-57 V PoE-In. It comes with a PoE injector, a power supply, and everything you need to secure it on a ceiling. FTC11XG runs a full version of SwOS Lite, and has its own switch chip, allowing you to perform a variety of tasks you would never expect from a regular media converter! And even advanced packet filtering with Access Control List - a powerful network tool that allows packet filtering, accounting, and VLAN tagging based on Layer 2, 3, and 4 protocol header field conditions.

Tasks- Interface management and monitoring- VLAN support- SNMP reporting- Basic traffic shaping  
Product specifications- Product code: FTC11XG- Dimensions: 254 x 97 x 35 mm- 10/100/1000 Ethernet ports: 1- CPU temperature monitor: Yes- Can be used indoors: Yes- Can be used outdoors: Yes- Certification: CE, EAC, ROHS- Cooling type: Passive- DC jack input Voltage: 18-57 V- IP: 55- Max power consumption: 10 W- Max power consumption without attachments: 9 W- Number of 1G/2.5G/5G/10G Ethernet ports: 1- Number of DC inputs: 2 (DC jack, PoE-IN)- PoE in: 802.3 bt- PoE in input Voltage: 43-57 V- SFP+ ports: 1- Storage size: 64 KB- Storage type: FLASH- Switch chip model: 88E6193- Tested ambient temperature: -40°C to 70°C

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

