

Item no.: 383722

L22UGS-5HAXD2HAXD-15S - Mikrotik L22UGS-5HaxD2HaxD-15S



from **156,69 EUR**

Item no.: 383722
shipping weight: 3.00 kg
Manufacturer: MikroTik

Product Description

Managing outdoor wireless networks has never been easier: mANTBox ax 15s can deliver unrivalled point-to-multipoint wireless connectivity to a wide range of devices over a distance of 20 kilometres! A powerful combination of modern dual-core ARM CPUs, our latest 802.11ax Wi-Fi 6 dual-band radios and powerful integrated sector antennas will take your signal stability, speed and responsiveness to the next level! There is a Gigabit Ethernet port with PoE input and an SFP port with 2.5 Gigabit support for extra fast fibre uplinks. There are several benefits to upgrading your setup to Wi-Fi 6. Speed: We have seen up to 40% faster speeds in the 5 GHz spectrum and up to 90% faster speeds in the 2.4 GHz spectrum. Security: WPA3 encryption and management frame protection prevent all types of attacks, such as brute forcing and WPA2 handshake capture deauthentication attacks. Reliability: The seamless, fast transition (roaming) enables an uninterrupted signal when you need to switch between access points. Wi-Fi 6 also ensures a fair distribution of data traffic when the connection is shared by a large number of users. Energy efficiency: Functions such as Target Wake Time reduce power consumption in the long term. Better for your wallet and the planet! mANTBox package contains everything you need: a Gigabit PoE injector, a power supply unit, a hose clamp and a mounting kit as well as the MikroTik quickMOUNT pro. This advanced wall mounting adapter allows you to rotate the antenna both horizontally and vertically by 140°. With the quickMOUNT pro it is possible to perfectly align the antenna using an integrated scale.

Specifications- Product code: L22UGS-5HaxD2HaxD-15S- Dimensions: 349 x 140 x 82 mm- Architecture: ARM 64bit- CPU: IPQ-5010- CPU core count: 2- CPU rated frequency: 800 MHz- RouterOS licence: 4- Operating system: RouterOS v7- RAM size: 256 MB- Memory size: 128 MB- Memory type: NAND- MTBF: Approximately 200,000 hours at 25°C- Tested ambient temperature: -40°C to 70°C- Power supply- Number of DC inputs: 2 (DC socket, PoE-IN)- DC socket input voltage: 12-28 V- Maximum power consumption: 21 W- Maximum power consumption without additional devices: 11 W- Cooling type: Passive- PoE in: Passive PoE- PoE input: Voltage 18-28 V- Wireless specifications- Wireless 2.4 GHz Maximum data rate: 574 Mbps- Wireless 2.4 GHz Number of chains: 2- Wireless 2.4 GHz standards: 802.11b/g/n/ax- Antenna gain dBi for 2.4 GHz: 12- Wireless 2.4 GHz chip model: IPQ-5010- Wireless 2.4 GHz generation: Wi-Fi 6- Wireless 5 GHz Max data rate: 2400 Mbit/s- Wireless 5 GHz Number of chains: 2- Wireless 5 GHz standards: 802.11a/n/ac/ax- Antenna Gain dBi for 5 GHz: 15- Wireless 5 GHz Chip Model: QCN-6102- Wireless 5 GHz Generation: Wi-Fi 6- Ethernet- 10/100/1000 Ethernet Ports: 1- Fibre- SFP Ports: 1 (2.5G supported)- Peripherals- Number of USB ports: 1- USB Power Reset: Yes- USB Slot Type: USB Type A- Maximum USB Current (A): 1.5- Other- PCB Temperature Monitoring: Yes- Voltage Monitoring: Yes- Beeper: Yes- Certification & Approvals- Certification: CE, FCC, IC, EAC, ROHS- IP: 55

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

