

Item no.: MFI-MSC

MFI-MSC - Ceiling Mount Motion Sensor

27,64 EUR

Item no.: MFI-MSC
shipping weight: 0.30 kg
Manufacturer: Ubiquiti



Product Description

mFi-MSC, Ceiling Mount Motion Sensor

mFi(TM) is a Machine-to-Machine management system from, Inc. The mFi hardware can be managed and monitored from the mFi Controller software. The mFi Controller software allows you to create rules that trigger actions based on data from your mFi sensors. For example, motion detection could turn a light on, or a high temperature reading could trigger a fan. The mFi platform is compatible with third-party devices, making the options unlimited!

mSensor(TM)

offers a variety of sensors to connect to the mPort and your mFi network. These sensors connect to the mPort using a standard RJ45 cable, except for the mFi-DS, which connects using a terminal block connector.

- mFi-MSW – Wall Mount Motion Sensor
- mFi-MSC – Ceiling Mount Motion Sensor
- mFi-THS – Temperature Sensor
- mFi-CS – Current Sensor
- mFi-DS – Door Sensor

Features

Plug and Play Installation

Use standard Ethernet cables to connect machines and sensors. Use Wi-Fi to seamlessly connect mFi nodes to your IP network. Unlimited device scalability. Powerful Functionality

Create powerful relationships between sensors, machines, and powered devices. Cloud and Mobile Support

Access multiple mFi networks from any remote location through a web browser. New devices can instantly be discovered and provisioned through the cloud. Sophisticated User Experience

From auto-detection of machines through intuitive and powerful rule creation, the mFi Controller transforms a machine network into an automated symphony.

Software

The mFi Controller software is designed to work with the mFi product line and third party devices. The software interface design is based on the popular and easy-to-use UniFi(TM) software interface. The mFi Controller software allows you to manage your mPort, mPower, mSensor, and third-party devices from your web browser.

Features

Machine Auto Detection

The mFi Controller software will auto-detect and provision mFi devices and connected machines on the machine network. Advanced Analytics

Powerful graphing with user-defined views provides in-depth analysis of the machine network. Events and Alerts

User-defined event recording and alerts provide feedback on machine network activity. Remote Control Capability

Remotely control the power and functionality of the machine network. Remote Terminal Support

Terminal command windows support unlimited machine network scalability through a single interface.

- Dimensions: 134.5 x 134.5 x 30.5 mm
- Weight: 136 g
- RF immunity: 10 V/m at 80 MHz to 2 GHz
- Warm time: 2 minutes
- Angle of view: 360°
- Cone of detection: 110° wide angle
- Ports: (1) mFi RJ45 port
- Mounting: Ceiling-mount bracket (included)
- Mounting height: Up to 4.5 m (15 ft.)
- Operating temperature: 0°C to 50°C
- Operating humidity: 5 to 95% condensing

System Requirements:

- Microsoft Windows 7, Windows Vista, Windows XP, Mac OS X, or Ubuntu Linux 12.04. 64-Bit operating system recommended (32-bit only supports 2 GBdatabase)
- Web Browser: Mozilla Firefox, Google Chrome, or Microsoft Internet Explorer 8 (or above)
- Java Runtime Environment 1.6 (1.6.0_26 or above recommended)
- Flash Player 10
- 2 GB RAM or higher is highly recommended

Specifications

**Scan this QR code to
view the product**

All details, up-to-date
prices and availability

