

Item no.: UVC-G3-FLEX

UVC-G3-FLEX - UniFi Video Camera G3 Flex, Full HD, IR, PoE

from **77,55 EUR**

Item no.: UVC-G3-FLEX shipping weight: 0.20 kg Manufacturer: Ubiquiti



Product Description

Ubiquiti UVC-G3-FLEX - UniFi Video Camera G3 Flex, Full HD, IR, PoE

The UniFi(R) Video Cameras G3 represent the next generation of cameras designed for use in the UniFi Video surveillance management system. These cameras offer 1080p Full HD resolution for day or night use and are integrated with the UniFi Video software for powerful and flexible, integrated IP video management.

The cameras are easy to operate and manage using the UniFi Video(R) software, which is pre-installed on the optional UniFi Application Server and the UniFi NVR appliance, or can be downloaded free of charge.

The UniFi Video Camera G3 Flex features a wideangle lens and 1080p video performance for expanded surveillance coverage. Mounting options include desktop, wall or pole mount for both indoor and outdoor installations. The infrared LEDs and automatic IR cut filter provide highquality day and night monitoring. The G3 Flex also provides an adjustable lens and swivel base for vertical and horizontal viewing angle adjustments. Features:

- 1080p full HD, 25 FPSEFL 3.4 mm, /1.2
- Wide-angle lens
- 802.3af PoE
- Built-in microphone
- Desktop, wall or pole mount
- Adjustable lens and swivel base for vertical and horizontal viewing angle adjustments
- Dimensions: 107.5 x 48 mm (4.23 x 1.89")
- Weight: 170 g (6 oz)
 Networking interface: (1) 10/100 Ethernet port
 Sensor: 1/3" 2-Megapixel HDR sensor
 Lens: EFL 3.4 mm, f/1.2

- Night mode: IR LEDs with mechanical IR filter Microphone: Yes
- Button: Factory reset button
- Power method: 802.3af PoEMaximum power consumption: 4 W

- Maximum power consumption: 4 W
 Mounting: Table/wall/pole
 Operating temperature: -20°C to 50°C (-4°F to 122°F)
 Operating humidity: 20 90% non-condensing
 Video compression: 1.264
 Resolution: 1080p full HD (1920x1080)
 Maximum frame rate: 25 FPS
 Image settings: Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz
 Viewing angle:
- Viewing angle:
- Lens correction off: 87.4° (H), 47° (V), 104° (D)
 Lens correction on: 80° (H), 46° (V), 92° (D)
 Supported UniFi Video version: UniFi Video 3.9.2 (or newer)
 UniFi Video system 400 DNM is 64-bit Microsoft Windows 10/8/7, Ubuntu 14.04 or 16.04, or Debian 7.0 System with an Intel or compatible 1.86 GHz (or above) processor and a minimum of 4 GB RAM
- Mobile apps: UniFi Video, iOS and Android

Scan this QR code to view the product

All details, up-to-date prices and availability

