

Item no.: BULLETAC-IP67

## BULLETAC-IP67 - Dual-band airMAX(R) AC radio with dedicated Wi-Fi management

114,<sup>04</sup> EUR

Item no.: BULLETAC-IP67 shipping weight: 0.20 kg Manufacturer: Ubiquiti



## Product Description

BulletAC-IP67 - Dual-band airMAX AC radio with dedicated Wi-Fi management

Please note: Only compatible with airMAX devices.

The Bullet AC is a fully integrated radio that delivers up to 300+ Mbps real TCP/IP throughput. Features

- Dual-band frequency: The Bullet AC covers both 2.4 and 5 GHz radio bands, covering a wide range of frequencies that work well for both short and long-distance
- Output power: The B-DB-AC offers up to 22 dBm of output power, while the BulletAC-IP67 offers 21 dBm.
   Passive Power over Ethernet (PoE): 24 V Passive PoE functionality is included. Both power and data are carried over a single Ethernet cable to the Bullet AC. Use a PoE adapter (not included) or an optional PoE switch.
- Weatherproof design: The durable casing of the Bullet AC can withstand natures harshest outdoor elements. The BulletAC-IP67 features a robust IP67 weather-resistant body that protects against dust and water.
- Plug and Play integration: No special tools or antennas are required to install the Bullet AC. Simply plug in and go.
- Dimensions: 190 x 46 mm (7.72 x 1.81")
  Weight: 190 g (6.70 oz)
  Enclosure: Aluminum and rubber
  Processor: MIPS 74KC
  Memory: DDR2 64 MB

- Memory: DDR2 64 MB
  Networking interface: (1) 10/100/1000 Ethernet port
  Antenna connector: N-Type connector
  Max. power consumption: 7 W
  Max. TX power: 21 dBm
  Power supply: 24 V, 0.3 A Gigabit PoE adapter
  Power method: 24 V passive PoE (pairs 4, 5+; 7, 8 return)
- ESD/EMP protection: +/-24 kV contact/air
- Operating temperature: -40°C to 70°C (-40°F to 158°F)

  Operating humidity: 5 to 95% non-condensing

  Certifications: CE, FCC, IC

## Specifications

