

Item no.: UNVR

UNVR - UniFi 4-Bay Network Video Recorder

from **351,85 EUR**

Item no.: UNVR
shipping weight: 5.20 kg
Manufacturer: Ubiquiti



Product Description

Ubiquiti UNVR - UniFi 4-Bay Network Video Recorder

Enterprise network video recorder, can provide up to 30 days of 4K video storage for 15 cameras or Full HD video storage for 50 cameras.

The UniFi(R) NVR is an enterprise network video recorder that integrates an NVR, the UniFi Protect software, and a 4-drive bay. UNVR unifies enterprise-class data protection and scalable storage with simple Plug-and-Play integration using the intuitive UniFi Protect software. From a desktop computer or mobile device, you can access your surveillance recordings from virtually anywhere using the intuitive graphical user interface. The mobile app is available for iOS and Android-based devices. The drive bays are easily accessed from the front panel, so hard drive mounting and maintenance are simple. Using four 8 TB drives in a RAID 5 configuration, the UNVR can provide up to 30 days of 4k video storage for 15 cameras or Full HD video storage for 50 cameras. Features:

- 4x 2.5"/3.5" drive bays
- 1x 10G SFP+ port
- 1x Gigabit RJ45 port
- 1U rackmountable (kit included)
- Plug-and-Play UniFi Protect system with NVR
- Automated secure RAID 1 or RAID 5 configuration
- Supports USP-RPS for PSU failover

- Dimensions: 442.4 x 325 x 43.7 mm (17.4 x 12.8 x 1.7")
- Weight: Without rackmount brackets: 5.11 kg (11.27 lb); With rackmount brackets: 5.20 kg (11.46 lb)
- Enclosure characteristics: SGCC Steel
- Processor: Quad-Core ARM Cortex-A57 at 1.7 GHz
- System memory: 4 GB DDR4
- On-board Flash storage: SPI NOR 32 MB, USB Flash 8 GB
- Max. power consumption: 100 W
- Max. power budget for drives: 75 W
- Power method: 1x universal AC input, 1x RPS DC input
- Power supply: 100-240 V AC, 50/60 Hz, 2 A
- Networking interfaces: 1x 10/100/1000 Mbps RJ45 Ethernet, 1x 1/10 Gbps SFP+ Ethernet
- Management interface: Ethernet in-band management
- ESD/EMP protection: Air: +/-12 kV, contact: +/-8 kV
- Operating temperature: -5°C to 40°C (23°F to 104°F)
- Operating humidity: 5% - 95% non-condensing
- LEDs: System: 1x power, blue/white (Flashing white: Bootup in progress, Flashing blue: Firmware upgrading, Steady white: Factory defaults, awaiting adoption); Ethernet: Steady blue: Device is adopted; SFP+ white: Green: 1000 Mbps, Amber: 10/100 Mbps; SFP+: White: 10 Gbps, Green: 1 Gbps; HDD: Amber: Disk error, White: Disk detected

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



