

Item no.: ES-18X-EU

ES-18X-EU - Gigabit Switch with PoE and SFP

from 181,41 EUR

Item no.: ES-18X-EU shipping weight: 1.50 kg Manufacturer: Ubiquiti



Product Description

Ubiquiti ES-18X - Gigabit Switch with PoE and SFP

Ideal for larger-scale WISP applications, the EdgeSwitch(R) 18X is an affordable high-performance switch with SFP ports and a fanless design. Sixteen Gigabit RJ45 ports offer copper connectivity with PoE input on port 1 and PoE passthrough on port 16. Two SFP ports offer fiber connectivity. The browser-based configuration interface offers intuitive control. Management is also available through the Ubiquiti(R) Network Management System (UNMS(TM)). Features:

- (16) Gigabit RJ45 ports(2) SFP ports

- Supports PoE passthrough on port 16 (software-selectable)
 Powered by 24 V passive PoE or external 24 V AC/DC adapter
- Wall or rack-mountable (bracket included)
- Dimensions: 299,8 x 160 x 43,7 mm (11,8 x 6,3 x 1,7")
- Weight: 1,15 g (2,54 lb.)
 Total non-blocking throughput: 18 Gbps

- Total non-blocking throughput: 18 Gbps
 Switching capacity: 36 Gbps
 Forwarding rate: 26.78 Mpps
 Max. power consumption (excluding PoE output): 14 W
 Power method: AC/DC adapter, 24 V passive PoE
 Supported voltage range: 9 30 V DC
 Power supply: 24 V DC, 1 A power adapter (included) or 24 V passive PoE
 LEDs per port: System status, RJ45 data ports link/speed/activity, SFP data ports link/activity
 Networking interfaces: (16) 10/100/1000 Mbps RJ45 ports, (2) 1 Gbps SFP ports
 Management interface: Efternet in-hand
- Management interface: Ethernet in-band
 Certifications: CE, FCC, IC
- ESD/EMP protection: Air: +/-16 kV; contact: +/-8 kV
 Operating temperature: -10°C to 50°C (14°F to 122°F)
 Operating humidity: -90% non-condensing



