

Item no.: USW-LITE-8-POE

USW-LITE-8-POE - UniFi Switch Lite 8 PoE

from **114,24 EUR**

Item no.: USW-LITE-8-POE

shipping weight: 0.80 kg

Manufacturer: Ubiquiti



Product Description

USW-Lite-8-PoE - UniFi Switch Lite 8 PoE

The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3af PoE+ that provide up to a total PoE wattage of 52 W for UniFi Access Points or other PoE devices.

Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.

Mechanical

- Dimensions: 99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25")
- Weight 450 g (15.87 oz)

Hardware

- Total non-blocking line rate: 8 Gbps
- Max. power consumption: 8 W
- Power method: 54 V DC, 1.1 A power adapter
- Power supply: External 54 V/60 W power adapter
- Supported voltage range: DC 50 V to 57 V
- Networking interfaces: (8) 10/100/1000 Mbps Ethernet RJ45 ports
- PoE interfaces: (4) PoE+ IEEE 802.3af/at (pins 1, 2+; 3, 6-)
- Management interface: Ethernet in-band
- Max. PoE+ wattage per port by PSE: 30 W
- Modes: SMB Layer 2 PoE Gigabit Ethernet Switch
- Operating temperature: -15°C to 40°C (5°F to 104°F)
- Operating humidity: 10 - 90% non-condensing
- Certifications: CE, FCC, IC

LED

- System: (1) Power, blue/white; Flashing white: Bootup in progress; Flashing blue: Firmware upgrading; Steady white: Factory defaults, awaiting adoption; Steady blue: Device is adopted
- Ethernet: Green: 1G; Amber: 10/100 Mbps
- PoE: Amber: IEEE 802.3af/at

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



