

Item no.: UISP-CABLE-C\_50

## Patchcable Cat.5, SF/UTP, 50m, black

from **31,92 EUR**

Item no.: UISP-CABLE-C\_50

shipping weight: 2.75 kg

Manufacturer: Ubiquiti



### Product Description

UISP-Cable-Carrier - Industrial-grade Ethernet Cat. 5e Cable, 50 m

Note: This is the same cable as TC-Carrier.

The UISP-Cable-Carrier is a category 5e cable that delivers multilayered elemental protection with a primary braid shield and a weatherproof jacket that prevents damage from rain, snow, and other harsh climatic conditions. The cable is also equipped with a drain wire and internal foil shielding to protect it from electrostatic discharge (ESD), and its anti-crosstalk divider preserves signal integrity, allowing the cable to maintain Gigabit Ethernet link rates even when electromagnetic interference is present.

- Cable length: 50 m (164 ft)
- Cable color: Black
- Cable type: Cat. 5e, shielded
- Ethernet support: Up to 1 Gbps
- Conductor wire gauge: 24 AWG
- Conductor: Solid bare copper
- Conductor diameter: 0.500 +/- 0.005 mm
- Insulation type: Solid polyethylene
- Insulation thickness: Avg. 0.295 mm; Min. 0.29 mm
- Insulation diameter: 1.16 +/- 0.02 mm
- Separation (polyester wrapping): Thick: 0.025 mm; Extent: 20 mm
- Anti-crosstalk divider: LDPE: 4.2 x 0.3 mm
- Cable shield (aluminum foil): Thick: 0.060 mm; Extent: 20 mm
- ESD drain wire: 0.4 TC
- Rip cord: Yes
- Secondary cable shield (braid): 16 x 8 x 0.16AA Density: 95%
- Jacket material: Polyethylene
- Jacket thickness: Avg. 0.52 mm; Min. 0.46 mm
- Jacket outer diameter: 6.8 +/- 0.30 mm
- Jacket color: Black
- Storage temperature: -30°C to 75°C (-22°F to 167°F)
- Installation temperature: -20°C to 60°C (-4°F to 140°F)
- Operation temperature: -40°C to 80°C (-40°F to 176°F)
- Standards: ANSI/TIA-568-C.2 (2009); ISO/IEC 11801 (Edition 2.2)

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

