

Item no.: USW-PRO-AGGREGATION

## USW-PRO-AGGREGATION-EU - UniFi Switch Pro Aggregation

from **893,80 EUR**

Item no.: USW-PRO-AGGREGATION  
shipping weight: 4.70 kg  
Manufacturer: Ubiquiti



### Product Description

#### UniFi Switch Pro Aggregation

The UniFi Switch Pro Aggregation utilizes high-bandwidth links to create link aggregation that enhances its switching capacity. The UniFi Switch Pro Aggregation is managed with the UniFi Network application (web and mobile), allowing you to easily build, scale, and monitor your enterprise networks.

#### Mechanical

- Dimensions: 442 x 325 x 44 mm (17.4 x 12.8 x 1.7")
- Weight: Without mount: 4.6 kg (10.14 lb.); With mount: 4.7 kg (10.36 lb.)
- Enclosure material: SGCC steel

#### Hardware

- Total non-blocking throughput: 380 Gbps
- Switching capacity: 760 Gbps
- Forwarding rate: 565.44 Mpps
- Max. power consumption: 100 W
- Power method: (1) universal AC input, 100-240 V AC, 2 A max., 50/60 Hz; (1) USP-RPS DC input, 11.5 V DC, 8.7 A
- Power supply: AC/DC, internal, 100 W
- Network interface: (28) 1/10 Gbps SFP+ Ethernet; (4) 1/10/25 Gbps SFP28 Ethernet\*
- LCM display: (1) 1.3" touchscreen; Bootup animation: Bootup in progress; Firmware upgrade icon: Firmware upgrading; Steady white: Factory defaults, awaiting adoption; Steady blue: Device is adopted
- LEDs: SFP28/SFP+: White, link and activity
- Management interface: Ethernet in-band
- Modes: SMB layer 3 10/25 G fiber switch
- ESD/EMP protection: Air: ±16 kV, contact: ±12 kV
- Operating temperature: -5°C to 40°C (23°F to 104°F)
- Operating humidity: 10 - 90% non-condensing
- Certifications: CE, FCC, IC

\*The four SFP28 ports don't support mixed speed at 25 Gbps mode. Once one of the SFP28 ports is configured at 25 Gbps mode, the others will be limited at 25 Gbps too. The SFP28 ports only support mixed speed when all ports are at 1 Gbps or 10 Gbps.

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

