

Item no.: 384773

UACC-DUAL-POWER-INJECTOR - UISP dual power injector, 100W, 2 wave models, 2.5 GbE connectivity

from **82,60 EUR**

Item no.: 384773
shipping weight: 0.30 kg
Manufacturer: Ubiquiti

Product Description

Versatile PoE adapter that delivers up to 100W to power any two Wave models and provides 2.5GbE connectivity. (2) 2.5G GbE RJ45 ports with 48V passive PoE. Weatherproof housing. Pole or wall mountable (kit included). Supports all Wave models. Mechanical- Dimensions: 145.5 x 95.5 x 44 mm (5.7 x 3.8 x 1.7")- Weight: 280 g (9.9 oz)- Housing material: UV-stabilised polycarbonate- Wind resistance: Up to 200 km/h (125 mph)- Wind load: 10.5 N at 200 km/h (2.4 lbf at 125 mph)- Mounting: pole mount 35 to 60 mm (1.37 to 2.36") on outside pipe diameter, wall mount- Weatherproof IPX5 Hardware- Network interface: (2) 2.5 GbE RJ45 ports- Power supply: (1) Power TransPort DC input 27V DC, 4.44A- Power supply: 120W Power TransPort Adapter (not included), UISP Power, UISP Power Pro- Output voltage: 48V DC- Max: Total 100W- LEDs Blue: Power On- Operating Temperature: -40 to 60° C (-40 to 140° F)- Humidity: 5 to 95% non-condensing- Certifications: CE, FCC, ICCompatibility- Supported models: Wave AP / Wave AP Micro / Wave Long-Range / Wave Nano / Wave Pro / Wave Pico

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

