

Item no.: UNVR-PRO

UNVR-PRO-EU - Network Video Recorder Pro

from **513,89 EUR**

Item no.: UNVR-PRO shipping weight: 9.50 kg Manufacturer: Ubiquiti



Product Description

UNVR-Pro - Network Video Recorder Pro

The UNVR Pro is a UniFi OS Console that runs the pre-installed UniFi Protect application and has a 7-drive hard disk drive (HDD) bay that offers the greatest storage capacity of any UniFi OS Console. The powerful, easy-to-use UNVR Pro can be deployed in minutes and support systems with up to 60 cameras. Combining the best features of Cloud and onsite surveillance systems, UniFi Protect gives you centralized, local, low-latency access to all of your live camera feeds and recordings, as well as remote access from anywhere in the world via unifi.ui.com and the Protect mobile app.

The UNVR Pro also offers expanded RAID configuration options for enhanced data protection, applying either RAID 1, 5, or 10 based on the number of HDDs installed. It's also equipped with a 1.3" touchscreen display for concise, convenient video event previewing. Mechanical

- Dimensions: 442 x 325 x 87 mm (17.4 x 12.8 x 3.4")
- Weight: Without rackmount brackets: 9.2 kg (20.28 lb); With rackmount brackets: 9.45 kg (20.83 lb)
 Enclosure material: SGCC steel
- Mount material: SGCC steel

Hardware

- Max. power consumption: 160 W
 Max. power budget for drives: 135 W
- Nata: power budget for onlyes. ISS W
 Power method: (1) Universal AC input, 100-240 V AC, 3 A max., 50/60 Hz; (1) USP-RPS DC input, 11.5 V DC, 13.91 A
 Power supply: AC/DC, internal, 200 W
 Networking interfaces: (1) 10/100/1000 Mbps RJ45 Ethernet; (1) 1/10 Gbps SFP+ Ethernet

- Networking interfaces: (1) 10/100/1000 Mbps RJ45 Ethernet; (1) 1/10 Gbps SFP+ Ethernet
 RF interface: (1) Bluetooth v4.1
 LCM display: (1) 1.3" touchscreen; Bootup animation: Bootup in progress; Firmware upgrade icon: Firmware upgrading; Steady white: Factory defaults, awaiting adoption; Steady blue: Device is adopted
 Management interface: Ethernet in-band management
 ESD/EMP protection: Air: ±12 kV, contact: ±8 kV
 Operating temperature: -5°C to 40°C (23°F to 104°F)
 Operating humidity: 5 95% non-condensing
 Certications: FCC, CE, IC

LEDs

- Ethernet: White: 10/100/1000 Mbps
 SFP+: White: 1/10 Gbps
 HDD: Amber: Disk error; White: Disk detected
- RPS: Blue: Ready

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

