

Item no.: UP-FLOODLIGHT

UP-FLOODLIGHT - Smart Flood Light

from **112,75 EUR**

Item no.: UP-FLOODLIGHT
shipping weight: 0.30 kg
Manufacturer: Ubiquiti



Product Description

UP-FloodLight - Smart Flood Light

Smart managed floodlight with integrated motion detection and light sensor. Housed in a compact, sleek design for low profile mounting. Easily setup and configure the UP-FloodLight with the UniFi Protect App.

Mechanical

- Dimensions: 135 x 65 x 50 mm (5.31 x 2.56 x 1.97")
- Weight: Without mount: 216 g (7.62 oz); With flat wall mount: 236 g (8.32 oz); With angle mount: 273 g (9.63 oz)
- Enclosure materials: Plastic, metal
- Mount materials: Flat wall mount: Plastic; Angle mount: Plastic
- Weatherproofing: IPX5

Hardware

- Processor: 24 Kc MIPS processor at 650 MHz
- Memory information: 64 MB DDR2
- Management interface: UniFi Protect
- Networking interface: 10/100 Mbps RJ45 Ethernet port
- Max. power consumption: 10.5 W
- Power method: 802.3af PoE
- Power supply: 802.3af PoE, 48 V DC, 0.22A max.
- ESD/EMP protection: Air: ±8 kV; Contact: ±8 kV
- Button: Factory reset
- RF: Bluetooth 4.0
- LEDs: R/B/W
- Operating temperature: -10°C to 45°C (14°F to 113°F)
- Operating humidity: 20 to 80% non-condensing
- Certifications: FCC, IC, CE

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

