

Item no.: POE-48-24W-WH

## POE-48-24W-WH - 48 V PoE Injector, white

from **11,19 EUR**

Item no.: POE-48-24W-WH  
shipping weight: 0.20 kg  
Manufacturer: Ubiquiti



### Product Description

POE-48-24W-WH - 48 V PoE Injector, white

offers Power over Ethernet (PoE) adapters to power a variety of products. The PoE adapters are compatible with most PoE devices, including: airFiber, airMAX, EdgeMAX, mFi, UniFi AP, UniFi Video/airVision.

- Dimensions: 93 x 59 x 33 mm (3.66 x 2.32 x 1.30")
- Weight: 145 g (5.12 oz.)
- Output voltage: 48 V DC @ 0.5 A
- LAN activity indicator: No
- Gigabit LAN port: No
- Remote reset capability: No
- Reset button: No
- Rated voltage: 100-240 V AC @ 50/60 Hz
- Input current: 0.6 A @ 120 V AC, 0.4 A @ 240 V AC
- Inrush current: <60 A peak @ 120 V AC, <120 A peak @ 230 V AC
- Efficiency: 80+%
- Output ripple: 1% max
- Switching frequency: 65 kHz
- Line regulation ? 3%
- Load regulation ? 5%
- 2-pair power supply: Pins 4, 5 (+) and pins 7, 8 (-)
- 4-pair power supply: -
- Operating temperature: 0°C to 40°C (32°F to 104°F)
- Storage temperature: -30°C to 70°C (-22°F to 158°F)
- Operating humidity: 5 to 90 % non-condensing
- AC connection: IEC-320 C6
- Data IN/POE: RJ45 shielded socket
- Surge protection: Differential and common mode
- Clamping protection: 11 V data, 60 V current
- Max. surge discharge: 1500 A (8/20 ?s) current
- Peak pulse current: 36 A (10/1000 ?s) data
- Shunt capacitance: <5 pF Data
- Response time: <1 ns
- Certifications: CE, FCC, IC, UL

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



