

Item no.: U6-MESH

U6-MESH - Access Point WiFi 6 Mesh

from 205,31 EUR

Item no.: U6-MESH shipping weight: 0.50 kg Manufacturer: Ubiquiti



Product Description

U6-Mesh - Access Point WiFi 6 Mesh

The Access Point WiFi 6 Mesh (U6 Mesh) is a high-performance, four-stream WiFi 6 access point that provides best-in-class signal meshing to enhance the wireless coverage of home and enterprise networks. The U6 Mesh can reach an aggregate throughput rate up to 5.3 Gbps with its 5 GHz (4x4 MU-MIMO and OFDMA) and 2.4 GHz (2x2 MIMO) bands. This access point also operates at full 4x4 MIMO with 160 MHz channels to create high-capacity wireless uplinks and facilitate faster data transfer. The sleek U6 Mesh is discreet enough to stage anywhere in your home or office, but also rugged enough to reliably operate outdoors thanks to its IPX5-rated, waterproof housing. The U6 Mesh is a plug-and-play device designed to easily extend your wireless signal to ensure full, seamless coverage and high-quality WiFi connectivity. It can be set up in minutes and fully managed with the UniFi Network web application or mobile app.

Mechanical

- Dimensions: Ø48.5 x 159.5 mm (Ø1.9 x 6.28")
 Weight: 400 g (0.88 lb)
 Enclosure material: Plastic, aluminum
 Mount materials: Plastic

- Weatherproofing: IPX5

Hardware

- Management interfaces: Ethernet, Bluetooth
 Networking interface: 1x GbE RJ45 port
 Button: Factory reset

- LED: White/blue
- Power method: 802.3af PoE
- Power method: 802.3ar PoE
 Power supply: UniFi PoE switch; 48 V, 0.32 A PoE adapter (included)
 Supported voltage range: 44 to 57 V DC
 Max. power consumption: 11.4 W
 Max. TX power: 2.4 GHz: 22 dBm; 5 GHz: 26 dBm
 MIMO: 2.4 GHz: 2x2 (UL MU-MIMO); 5 GHz: 4x4 (DL/UL MU-MIMO)
 Throughput rate: 2.4 GHz: 573.5 Mbps; 5 GHz: 4.8 Gbps
 Antenna gain: 2.4 GHz: 3 dBi; 5 GHz: 5 dBi
 Mounting Well decided page to the included by Coiling mount (option)

- Afriefina gain: 2.4 GHz; 3 dBi, 3 GHz; 3 dBi
 Mounting: Wall, desktop, pole mount (included); Ceiling mount (optional)
 Operating temperature: -30°C to 60°C (-22°F to 140°F)
 Operating humidity: 5 95% non-condensing
 Certifications: CE, FCC, IC

Software

- WiFi standards: 802.11a/b/g; WiFi 4/WiFi 5/WiFi 6
 Wireless security: WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)
- BSSID: 8 per radioVLAN: 802.1Q
- Advanced QoS: Per-user rate limiting
- Guest traffic isolation: Supported
 Concurrent clients: 300+
- Zero wait DFS: Yes

^{*}Supported with upcoming firmware versions

Scan this QR code to view the product All details, up-to-date prices and availability

