

Item no.: UISP-S

## UISP-S-EU - UISP Gigabit PoE Switch

**136,66 EUR**

Item no.: UISP-S  
shipping weight: 0.80 kg  
Manufacturer: Ubiquiti



### Product Description

#### Ubiquiti UISP-S - UISP Switch

Ideal for wireless ISP (WISP) deployments, the UISP™ Switch is a fanless, Layer 2 PoE switch with 8x GbE RJ45 ports and 1x 1G SFP port for an additional fiber uplink option. The UISP Switch is a cost-effective solution for WISPs looking to quickly and inexpensively deliver Gigabit wireless speeds to their customers. With its hefty 110 W total PoE supply, the UISP Switch delivers substantial power to every radio in your service network. For larger deployments, pair it with the UISP Console to create a cohesive routing and switching hub. The UISP Switch is managed with the UISP application, a centralized platform where you can monitor and manage all of your UISP devices.

#### Mechanical

- Dimensions: 210.4 x 95 x 29 mm (8.28 x 3.74 x 1.14")
- Weight: 610 g (1.34 lb)
- Enclosure material: Polycarbonate

#### Hardware

- Total non-blocking throughput: 9 Gbps
- Switching capacity: 18 Gbps
- Forwarding rate: 13.392 Mpps
- Networking interface: 8x 10/100/1000 MbE RJ45 ports; 1x 1G SFP port
- Management interface: Ethernet in-band; Bluetooth BLE
- Power method: External AC/DC adapter
- Power supply: 27 V DC, 4.4 A power adapter (included)
- Supported voltage range: 24 - 28 V DC
- Max. power consumption: 8 W (excludes PoE output)
- ESD/EMP protection: Air: ±15 kV; Contact: ±8 kV
- Operating temperature: -10°C to 50°C (14°F to 122°F)
- Operating humidity: 5 to 95% non-condensing
- Certifications: CE, FCC, IC

#### PoE

- PoE interface: 8x 27 V passive PoE: 2-pair (pins 4, 5+/7, 8-) or 4-pair (pins 1, 2, 4, 5+/3, 6, 7, 8-)
- Max. Passive PoE wattage per port: 30 W/27 V DC
- Passive PoE voltage range: 27 V DC

#### LEDs

- System: Status
- RJ45 data ports: PoE; Speed/link/activity
- SFP data port: Link/activity

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



