

Item no.: UVC-AI-360

## UVC-AI-360 - UniFi Camera AI 360 with a Fisheye Lens and IR LEDs

from **433,92 EUR**

Item no.: UVC-AI-360  
shipping weight: 0.80 kg  
Manufacturer: Ubiquiti



### Product Description

#### UVC-AI-360 - UniFi Camera AI 360

The Camera AI 360 (AI 360) is a pan-tilt-zoom (PTZ) camera that provides panoramic, overhead surveillance of heavily populated indoor and outdoor areas. The AI 360 streams sharp 1920x1920 video at a smooth 30 frames per second (FPS), and its built-in IR LEDs ensure that every frame is crystal clear—day or night. Equipped with a 5 MP CMOS sensor and an ultra-wide, 360° fisheye lens, the AI 360 can quickly detect finite details within its expansive coverage area and capture them with pristine clarity. It's also protected with rugged, weather and tamper-resistant housing, making it an ideal choice for shopping centers, parking lots, airports, train stations, and other transportation hubs. The AI 360 is a sophisticated, feature-rich camera, but it's also designed to be incredibly easy to set up and incorporate into existing Protect deployments. It can be adopted in minutes and managed with either the UniFi Protect web application or mobile app.

#### Mechanical

- Dimensions: Ø147 x 49 mm (Ø5.77 x 1.94")
- Weight: Without mount: 655 g (1.44 lb); With outdoor accessory: 685 g (1.51 lb)
- Enclosure materials: Aluminum alloy, polycarbonate, hard-coated dome
- Mounting materials: Polycarbonate, stainless steel
- Weatherproofing: IPX4
- Resistance: IK08

#### Optics

- Sensor: 5 MP CMOS sensor
- Lens: Fisheye lens
- View angle: 360°
- Night mode: Built-in IR LED illumination and IR cut filter

#### Video

- Video compression: H.264, MJPG
- Resolution: 1920 x 1920 (1:1)
- Maximum frame rate: 30 FPS
- Image settings: Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, masking, text overlay

#### System

- Processor specs: ARM® quad-core Cortex™-A53
- Memory information: 2 GB LPDDR4
- Flash memory support: 8 GB eMMC
- Management interface: UniFi Protect
- Networking interface: GbE RJ45 port
- Power method: 802.3af PoE
- Power supply: 48 V DC, 0.18 A PoE
- Max. power consumption: 8.64 W
- Supported voltage range: 37 to 57 V DC
- Link/activity LED: Yes
- Button: Factory reset
- Operating temperature: -20°C to 40°C (-4°F to 104°F)
- Operating humidity: 10 to 90% noncondensing
- Certifications: FCC, IC, CE

#### Audio

- Microphone: Yes (can be disabled in software)
- Speaker: Yes

#### Software

- UniFi OS application: UniFi Protect
- Mobile apps: UniFi Protect iOS and Android

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

