

Item no.: LBE-5AC-LR-5_EU

LBE-5AC-LR-5 - LiteBeam 5AC, Long-Range, 5-Pack

from **510,34 EUR**

Item no.: LBE-5AC-LR-5_EU
shipping weight: 5.00 kg
Manufacturer: Ubiquiti



Product Description

Ubiquiti LBE-5AC-LR-5 - LiteBeam 5AC, Long-Range, 5-Pack

PLEASE NOTE: THIS IS A 5-PACK!

The LiteBeam 5AC Long Range is an affordable airMAX AC CPE designed for long-distance links. Reach new customers and still maintain your great ROI.

Mechanical

- Dimensions: 512 x 385.75 x 258.3 mm (20.18 x 15.19 x 10.17")
- Weight: Without mount: 1.360 kg (2.998 lb); With mount: 1.735 kg (3.825 lb)
- Enclosure materials: Aluminum, plastic
- Mounting: Pole-mounting kit (included)
- Wind loading: 550 N at 200 km/h (123.6 lbf at 125 mph)
- Wind survivability: 200 km/h (125 mph)

Hardware

- Networking interface: (1) 10/100/1000 Ethernet port
- Processor: MIPS 74Kc
- Memory: 64 MB DDR2
- Power supply: 24 V, 0.3 A Gigabit PoE adapter (included)
- Max. power consumption: 7 W
- Power method: Passive PoE (pairs 4, 5+; 7, 8 return)
- Supported voltage range: 24 V \pm 10%
- Gain: 26 dBi
- LEDs: Power, Ethernet
- Channel sizes: PtP mode: 10/20/30/40/50/60/80 MHz; PtMP mode: 10/20/30/40 MHz
- ESD/EMP protection: \pm 24 kV contact/air
- Operating temperature: -40°C to 70°C (-40°F to 158°F)
- Operating humidity: 5 to 95% non-condensing
- Certifications: CE, FCC, IC

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

