

Item no.: UVC-AI-BULLET

UVC-AI-BULLET

from **449,66 EUR**

Item no.: UVC-AI-BULLET

shipping weight: 0.90 kg

Manufacturer: Ubiquiti



Product Description

The Camera AI Bullet is a next-generation UniFi Protect camera that captures crisp 4MP (2688 x 1512) video at 30 FPS video over a Gigabit Ethernet connection. Equipped with infrared LEDs and an automatic IR cut filter, the camera also provides pristine nighttime video to deliver high-quality surveillance around the clock. The AI Bullet also features a built-in microphone to enhance your stream with crystal-clear audio.

Designed to be versatile and simple to deploy, the AI Bullet comes with a flexible, three-axes ball joint that makes it easy to position the camera exactly where you need it. This PoE-powered camera can be adopted in minutes with the UniFi Protect web application or mobile app.

- Streams 4MP (2688x1512) video at 30 FPS
- Built-in IR LEDs and an automatic IR cut filter for enhanced night vision
- Powered with PoE (37—57V DC)
- Smart detection range: People (<10 m) / Vehicles (<20 m)

Mechanical

- Dimensions Without mount: Ø82 x 88.3 mm (Ø3.23 x 3.48")
- With wall mount: Ø82 x 153 mm (Ø3.23 x 6.02")
- Weight Without mount: 628 g (1.38 lb)
- With wall mount: 765 g (1.69 lb)
- Enclosure materials Aluminum alloy, polycarbonate
- Mounting materials Wall mount: aluminum alloy
- Pole mount: aluminum alloy
- Weatherproofing IP65
- Resistance IK04

Optics

- Sensor 5 MP CMOS sensor
- Lens Fixed focal length
- View angle H: 84.7°, V: 46.2°, D: 99°
- Night mode IR LED illumination and an IR cut filter

Video

- Video compression H.264, MJPG
- Resolution 4MP (2688 x 1512), 16:9 aspect ratio
- Maximum frame rate 30 FPS
- Image settings Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz

System

- Processor specs Quad core Arm® Cortex®-A53 based chip
- Memory information 2 GB LPDDR4
- Management interface UniFi Protect application
- Networking interface 10/100/1,000 MbE RJ45
- Flash memory support 8GB eMMC
- Max. power consumption 7.68W
- Power method PoE
- Supported voltage range 37-57VDC
- LED R/G/B/W ring
- Button Factory reset
- Mounting Wall, pole mount (included)
- Operating temperature -20 to 40° C (-4 to 104° F)
- Operating humidity 10 to 90% noncondensing
- Certifications FCC, IC, CE

Audio

- Microphone Yes (can be disabled)
- Software
- UniFi OS application UniFi Protect
- Mobile app UniFi Protect (iOS and Android)

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

