

Item no.: UVC-G4-DOME-3_EU 4MP UniFi Protect Camera for ceiling mount applications, 3-pack





Product Description

High-resolution PoE camera designed for overhead and wide-area surveillance.

- 4 MP, 24 FPS camera
- Built-in infrared LEDs for nighttime surveillance
 IPX4-rated, weatherproof enclosure with IK08-rated vandal resistance
- Built-in microphone
 Ceiling or wall-mountable

PLEASE NOTE: THIS IS A 3-PACK! Mechanical

- Dimensions: Ø 109.2 x 64.5 mm (Ø4.3 x 2.5")
 Weight: Without mount: 370 g (13.05 oz); With mount: 390 g (13.76 oz)
 Enclosure materials: Aluminum alloy, polycarbonate, hard-coated dome
 Mounting materials: Polycarbonate, stainless steel
 Weatherproofing: IPX4
 Desire the polycarbonate

Resistance: IK08

Optics

- Sensor: 5 MP CMOS sensor
 Lens: Fixed focal length
 View angle: H:102.4°, V:71.4°, D:134.3°
 Night mode: Built-in light sensor; Built-in IR LED illumination and IR cut filter

Video

- Video compression: H.264

- Resolution: 2688 x 1512 (16:9)
 Maximum frame rate: 24 FPS
 Image settings: Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz

System

- Processor specs: Quad-core Arm® Cortex®-A53 based chip
 Memory information: 512 MB
 Management interface: UniFi Protect
 Networking interface: GbE RJ45 port
 Flash memory support: 256 MB
 Max. power consumption: 5 W
 Power method: PoE
 Supported voltage range: 44 to 57 V DC
 Link/activity LED: Yes
 Button: Factory reset
 Operating temperature: -20°C to 40°C (-4°F to 104°F)
 Operating humidity: 0 to 90% non-condensing
 Certifications: FCC, IC, CE

Audio

- Microphone: Yes (can be disabled in software)
 Speaker: Yes

Software

- UniFi OS application: UniFi Protect
 Mobile apps: UniFi Protect iOS and Android
- **B**Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

