

Item no.: UVC-G4-DOME-3_EU

4MP UniFi Protect Camera for ceiling mount applications, 3-pack

from **567,38 EUR**

Item no.: UVC-G4-DOME-3_EU

shipping weight: 2.61 kg

Manufacturer: Ubiquiti

Product Description

High-resolution PoE camera designed for overhead and wide-area surveillance.

- 4 MP, 24 FPS camera
- Built-in infrared LEDs for nighttime surveillance
- IPX4-rated, weatherproof enclosure with IK08-rated vandal resistance
- Built-in microphone
- Ceiling or wall-mountable

PLEASE NOTE: THIS IS A 3-PACK!

Mechanical

- Dimensions: Ø 109.2 x 64.5 mm (Ø4.3 x 2.5")
- Weight: Without mount: 370 g (13.05 oz); With mount: 390 g (13.76 oz)
- Enclosure materials: Aluminum alloy, polycarbonate, hard-coated dome
- Mounting materials: Polycarbonate, stainless steel
- Weatherproofing: IPX4
- Resistance: IK08

Optics

- Sensor: 5 MP CMOS sensor
- Lens: Fixed focal length
- View angle: H:102.4°, V:71.4°, D:134.3°
- Night mode: Built-in light sensor; Built-in IR LED illumination and IR cut filter

Video

- Video compression: H.264
- Resolution: 2688 x 1512 (16:9)
- Maximum frame rate: 24 FPS
- Image settings: Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz

System

- Processor specs: Quad-core Arm® Cortex®-A53 based chip
- Memory information: 512 MB
- Management interface: UniFi Protect
- Networking interface: GbE RJ45 port
- Flash memory support: 256 MB
- Max. power consumption: 5 W
- Power method: PoE
- Supported voltage range: 44 to 57 V DC
- Link/activity LED: Yes
- Button: Factory reset
- Operating temperature: -20°C to 40°C (-4°F to 104°F)
- Operating humidity: 0 to 90% non-condensing
- Certifications: FCC, IC, CE

Audio

- Microphone: Yes (can be disabled in software)
- Speaker: Yes

Software

- UniFi OS application: UniFi Protect
- Mobile apps: UniFi Protect iOS and Android

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

