

Item no.: UVC-G5-DOME

Camera G5 Dome



from 184,60 EUR

shipping weight: 0.50 kg Manufacturer: Ubiquiti

Product Description

Next-gen 2K HD PoE ceiling camera with enhanced dynamic range and low-light performance. Features:

- 2K HD, 30 FPS camera with a 5MP CMOS sensor
- Wide-angle view (102.4?)
 Weatherproof IPX4-rated enclosure with IK08-rated vandal resistance
 Improved low-light performance and IR night vision up to 10 m

Mechanical

- Dimensions: Ø109.2 x 64.5 mm (Ø4.3 x 2.5")
 Weight: Without mount: 370 g (13.05 oz); With mount: 390 g (13.76 oz)
 Enclosure materials: Aluminum alloy, polycarbonate, hard-coated dome
 Mount materials: Polycarbonate, stainless steel
 Weatherproofing: IPX4
 Positive of IVO9
- Resistance: IK08

Optics

- Sensor: 5MP CMOS sensor
 Lens: Fixed focal length
 View angle: H: 102.4°; V: 71.4°; D: 134.3°
 Night mode: Built-in IR LED illumination and IR cut filter

Video

- Video compression: H.264, MJPEG

- Resolution: 2688 x 1512 (16:9)

 Max. frame rate: 30 FPS

 Image settings: Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

- Processor: Dual-core Arm® Cortex®-A7 based chip
 Networking interface: 10/100 MbE RJ45 port
 Max. power consumption: 5 W
 Power method: PoE
 Supported voltage range: 37–57 V DC
 LED: R/G/B/W
 Button: Factory reset
 Mounting: Wall, ceiling mount
 Operating temperature: -20°C to 40°C (-4°F to 104°F)
 Operating humidity: 0 to 90% non-condensing
 Certifications: FCC, IC, CE

Audio

- Microphone: Yes (can be disabled)Speaker: Yes

Software

- UniFi OS application: UniFi Protect
 Mobile app: UniFi Protect iOS™ and Android™

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

