

Item no.: UA-G2-SK-PRO

UA-G2-SK-Pro, Smart Door System

from **641,66 EUR**

Item no.: UA-G2-SK-PRO
shipping weight: 0.50 kg
Manufacturer: Ubiquiti



Product Description

Hit the ground running on Access with a pro experience for a door, featuring two readers.

- (1) UniFi Access Door Hub
- (1) Access Reader G2 Professional
- (1) Access Reader G2 for door exit or entrance for additional door
- (2) UniFi Access pocket key fob

UA-Hub-Door Mechanical

- Dimensions 174.9 x 126 x 32.9 mm (6.9 x 5 x 1.3")
- Weight 363 g (12.8 oz)
- Enclosure material
- Polycarbonate
- Mounting material
- Polycarbonate

Hardware

- Networking interface
- (5) 10/100/1000 Base-T
- Power method
- PoE++
- UL 294 Power-limited Class 2 PSU
- UL 60950/62368 LPS/PS2 PSU
- Max. power consumption
- Without PoE output: 30W
- With PoE output: 50W
- PoE input
- 50V DC, 1A
- PoE output
- PoE passthrough, (4) PoE, 50V DC, total 20W
- Button
- (1) Factory-reset
- LEDs
- System: white/blue
- Output relays: white
- Digital input
- Request to exit/request to enter/remote release/door position sensor
- Dry output relay
- Lock: 30V DC, 1A
- Aux: 30V DC, 1A
- Powered output relay
- Lock: 12V DC, 1A
- Aux: 12V DC, 0.33A
- 12V DC, 0.33A
- Operating environment
- Indoor use only
- Operating temperature
- 0 to 40° C (32 to 104° F)
- Operating humidity
- 5 to 95% noncondensing
- UL 294 level
- Destructive attack: Level I
- Line security: Level I
- Endurance: Level I
- Standby power: Level I
- UL 294 statement
- Compliance with IEEE 802.3 (at or af) specifications was not verified as part of UL 294.
- The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.
- CAN/ULC-60839-11-1 Grade
- Grade assignment: 1
- Certifications
- CE, FCC, IC, UL 294, CAN/ULC-60839-11-1
- Document number, and issue date and/or revision level
- UA-Hub-Door002, V01

LEDs

- PoE in Steady blue: Adopted/device is ready
- Steady white: Pending adoption
- Blinking white/blue: Upgrading firmware
- PoE out Off: Not connected or no data link
- Steady blue: Connected and data link on

UA-G2-Pro Mechanical

- Dimensions 160 x 40.4 x 40.55 mm (6.3 x 1.59 x 1.6")
- Weight 136 g (4.8 oz)
- Enclosure material Polycarbonate, glass
- Mount material Aluminum alloy
- Mounting Wall, gang box
- Weatherproofing IP55

Hardware

- Networking interface (1) 10/100/1,000 MbE RJ45 port
- Connectivity BLE 4.2
- NFC
- Power method PoE
- Supported voltage range 48V DC
- Max. power consumption 6W
- ESD/EMP protection Air: ±15kV, contact: ±8kV
- Sensor ToF sensor
- Camera 4000 x 3000, 12 MP, 30 FPS
- Microphone Yes
- Speaker (1) 4 ohm, 1.5W
- LEDs R/G/B/W
- Flash
- Button (1) Factory-reset
- NFC frequency 13.56 MHz
- NFC read range < 30 mm
- NFC standards ISO 14443A, 14443B, 15693
- NFC technology NFC Tag 1,2,3,4,5
- MIFARE Classic
- MIFAREPlus
- MIFARE Ultralight
- MIFARE DESFire
- Operating temperature -10 to 40° C (14 to 104° F)
- Operating humidity 5 to 90% noncondensing
- Certifications CE, FCC, IC

UA-G2 Mechanical

- Dimensions 93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")
- Weight 82 g (2.9 oz)
- Enclosure material Polycarbonate, glass
- Mounting In wall, gang box
- Weatherproofing IP55

Hardware

- Networking interface (1) 10/100 MbE RJ45 port
- Connectivity BLE 4.1
- Power method PoE
- Supported voltage range 48V DC
- Max. power consumption 5W
- ESD/EMP protection Air: ±15kV, contact: ±8kV
- Sensors Proximity sensor
- Speaker (1) 8 ohm, 0.7W
- LEDs R/G/B/W
- Button (1) Factory-reset
- NFC frequency 13.56 MHz
- NFC read range < 30 mm
- NFC standards ISO 14443A, 14443B, 15693
- NFC technology NFC Tag 1,2,3,4,5
- MIFARE Classic
- MIFAREPlus
- MIFARE Ultralight
- MIFARE DESFire
- Operating temperature -30 to 45° C (-22 to 113° F)
- Operating humidity 5 to 90% noncondensing
- Certifications CE, FCC, IC

UA-Pocket Mechanical

- Dimensions 84 x 39 x 7.4 mm (3.3 x 1.5 x 0.29")
- Weight 16 g (0.56 oz)
- Enclosure material Polycarbonate, stainless steel
- Weatherproofing IP54

Hardware

- NFC frequency 13.56 MHz
- NFC technology ISO/IEC 14443 Type A
- MIFARE DESFire EV3 4K
- UniFi Access Proprietary Security Protocol
- Operating temperature -10 to 45° C (14 to 113° F)
- Operating humidity 10 to 90% noncondensing
- Certification CE

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

